Xpress YLSR Sanna Lightbar

One Table One Plug

Lightbar provides a truly unique lighting experience through its shape and angles that transforms from a companion ambient light to a work-focused task light.

What's Included

1 Sanna Lightbar, specified base and specified power adapter.

Notes

High output LED light engine

Color temperature of 3000K

50,000 hour lifespan

Luminosity of 610 lumens

Color Rendering Index of 90+CRI

Luminance of 2500 lux

75 lm/W

Power consumption of 8w

6' cord with detachable power adapter

Common power adapter used for detachable North American (A), Europlug (C) and UK (G) plug faces (when specified)


UL Listed


6 hour auto shut-off

One Table One Plug product offering plug style (D) refers to the DC power connection to be plugged into the DC Power Hub.

Xpress Available through Teknion's Xpress Program.







Freestanding Edge Clamp Thru Mount

PRODUCT OPTIONS

	Base Style	Style Insert Style Country of Installation Lightbar Finish		Plug Style					
1	Freestanding	N000	No Insert	_ A	Canada/U.S.A.	25 Cris	p Grey	_ D	DC Power Connection
2	Edge Clamp	4007	Heather Felt			60 Plati	inum	s	Standard with Power
3	Thru Mount	4046	Fine Grain			68 Antl	hracite		Adapter

SAMPLE ORDER CODE

YLSR 2	N000	A	68	D
--------	------	---	----	---

BASE STYLE PRICING

	DC Power Connection	Standard with Power Adapter	
Freestanding	798	861	
Edge Clamp	730	794	
Thru Mount	730	794	