height-adjustability

Xpress

Y W D

Navigate Height-Adjustable Built-in Gable Base - Parallel Planning



Navigate Height-Adjustable Built-in Gable Base - Parallel Planning is to be paired with Parallel Rectangular Height-Adjustable Built-in Worksurface, Gable, to create a District specific gable leg integrated height-adjustable table supporting parallel planning.

WHAT'S INCLUDED

1 Height-Adjustable base, leg and foot configuration as specified.

Electric base mechanism has 0.1 Watt resting power draw and uses 120V North

Vertical Wire Carrier includes cross channel bracket and mounts into credenza.

The height-adjustable worksurface must be specified separately.

For Switch details, see the Application Guide section.

Cross Channel Integrated Powerbar option (C) includes 3 outlets + 1 IEC Connection. This IEC connection accepts only one IEC-compatible power accessory (with an IEC cord terminal) at a time.

Undersurface cable management option (5) - Dual Plastic Trays + Powerbar with IEC refers to a Power Rod (with IEC cord terminal) that must be plugged into the IEC connection of the Cross Channel Integrated Powerbar option (C)

For more information about the One Table One Plug electrical system, IECcompatible power accessories and planning with IEC Connection, refer to Complements: Teknion's Ergonomics & Accessories Program.

Xpress Water Fall Finish Flintwood and Natural Veneer are excluded from Teknion's Xpress Program.

PRODUCT OPTIONS

	Leg Application	Base Mechanism	Actual Depth	Actual Width	Base Finish	Water Fall Finish
GZL	Left in Perpendicular Credenza, Gable toward Middle	78 Standard Electric	29	46, 52, 58, 64,	Foundation	Foundation
GZR	Right in Perpendicular Credenza, Gable toward Middle	(27" - 43")		70, 76, 82	Mica	Flintwood
GDL	Left Gable toward outside, Right T-Leg in Shared Perpendicular Credenza	9C Extended Electric- Restricted (25" - 48.7")			Accent	Natural Veneer
GDR	Right Gable toward outside, Left T-Leg in Shared Perpendicular Credenza	(2) - 40./)				

SAMPLE ORDER CODE

YWD GZL	9C	29	58	52	VZ
---------	----	----	----	----	----

PRODUCT OPTIONS (CONTINUED)

Switch Style	Switch Finish	Powerbar	Undersurface Cable Management	Vertical Wire Carrier (optional)
S Standard Up/Down	E Ebony Coordinate	N None	N None	N None
 Display with Up/Do Memory T Toggle Up/Down X Display Toggle with Memory and Naviga 	7 Platinum6 Crisp Grey	 I Cross Channel Integrated 4 Outlets C Cross Channel Integrated 3 Outlets + 1 IEC 	 Cable Organizer with Felt Cover Dual Plastic Trays and Powerbar Dual Plastic Trays Dual Plastic Trays+Powerbar with IEC 	 E Ebony Coordinate Platinum Coordinate Very White Coordinate

SAMPLE ORDER CODE (CONTINUED)

X X	I	1	N
-----	---	---	---

See pricing in the following page.

Xpress Y W D

Navigate Height-Adjustable Built-in Gable Base - Parallel Planning (Continued)

DIMENSIONS INCHES / MM

PRICING

		STANDARD ELE	CTRIC	
D	W	Foundation	Mica/Accent	
29 / 737	46 / 1168	4938	5044	
29 / 737	52 / 1321	4997	5103	
29 / 737	58 / 1473	5031	5137	
29 / 737	64 / 1626	5110	5215	
29 / 737	70 / 1778	5152	5258	
29 / 737	76 / 1930	4842	4949	
29 / 737	82 / 2083	4873	4980	

EXTENDED ELECTRIC-RESTRICTED

		Foundation	Mica/Accent	
29 / 737	46 / 1168	5333	5439	
29 / 737	52 / 1321	5394	5500	
29 / 737	58 / 1473	5433	5537	
29 / 737	64 / 1626	5473	5577	
29 / 737	70 / 1778	5516	5622	
29 / 737	76 / 1930	5212	5318	
29 / 737	82 / 2083	5245	5351	

If Flintwood Water Fall Finish is specified,

46" Width	830
52" Width	793
58" Width	872
64" Width	997
70" Width	1078
76" Width	851
82" Width	929

If Natural Veneer Water Fall Finish is specified,

46" Width	897
52" Width	863
58" Width	948
64" Width	1078
70" Width	1163
76" Width	942
82" Width	1024

If Display with Up/Down Memory (D) switch is specified, add 184

If Display Toggle with Memory and Navigate GPS (X) switch is specified, add 184

If No Power Bar, Dual Plastic Trays are specified, add 59

If No Power Bar, Dual Plastic Trays + Powerbar are specified, add $285\,$

If No Power Bar, Cable Organizer with Felt Cover is specified, add 292

If Cross Channel Integrated Powerbar - 4 Outlets (I) or 3 Outlets + 1 IEC (C) with No Cable Management is specified, add 247

 $If\ Cross\ Channel\ Integrated\ Powerbar\ -4\ Outlets\ (I)\ or\ 3\ Outlets\ +\ 1\ IEC\ (C)\ +\ Dual\ Plastic\ Trays\ are\ specified,\ add\ 308$

If Cross Channel Integrated Powerbar - 4 Outlets (I) + Dual Plastic Trays + Powerbar are specified, add 533

 $If\ Cross\ Channel\ Integrated\ Powerbar\ -\ 3\ Outlets +\ 1\ IEC\ (C) + Dual\ Plastic\ Trays +\ Powerbar\ with\ IEC\ are\ specified,\ add\ 605$

If Cross Channel Integrated Powerbar - 4 Outlets (I) or 3 Outlets + 1 IEC (C) + Cable Organizer with Felt Cover are specified, add 541

If Vertical Wire Carrier is specified, add 334