





## BEEPC

## Power Qube

One Table  
One PlugConnector and  
Cord Type

Plug-In (A)



IEC Connector (C)

This product is mounted above a worksurface with Square Cut-Out and fixed inside Square Grommet Ring. It is used to provide quick power, data and USB access at the worksurface level.

## WHAT'S INCLUDED

1 power qube, 1 twistable attachment ring and 1 square grommet ring.

## NOTES

Must be installed in Square Grommet Ring.

Data Faceplate **not** included (if specified).

The Square Cut-Out mounting option can be specified on worksurface to allow Power Qube installation.

IEC Connector option (C) can only be used in combination with a Height-Adjustable Worksurfaces.

For more information about IEC Connector option (C), refer to One Table One Plug Application Guide in Complements: Teknion's Ergonomics & Accessories Programm. Simplex outlet finish to be Soft Gris.

Power Cord is a grey cloth covered type.

Each USB Outlet has one USB-A port and one USB-C port for charging only.

The USB-A port always supplies 10 Watts maximum at 5 Volts DC when used alone.

## Standard USB-C Capacity (S):

The USB-C port supplies 18 Watts maximum at 5 to 12 Volts DC when used alone.

Maximum combined output is 15 Watts when both ports are used together: 5 Watts for USB-A port and 10 Watts for USB-C.

## High USB-C Capacity (H):

The USB-C port supplies 65 Watts at 5 to 20 Volts DC when used alone.

Due to limitations with transformer design, the maximum combined output is 30 Watts when both ports are used together: 10 Watts for USB-A port and 20 Watts for USB-C port

This reduced output in dual port mode **will not** support charging of laptops or quick charging of some phones/tablets that require more than 5 Volts DC.

The USB-C port will charge laptops up to 65 Watts and support Quick Charge when used in single port mode.

## PRODUCT OPTIONS

Plug Type	Configuration		Mounting Option	Power Cord Length (Inches)	Country of Installation	Case and Front Finish
A Plug-In  C IEC Connector	<b>D101N</b>	Dual – 1 Power / 0 USB / 1 Data	D Desk Edge Clamp  Q Square Cut-Out	048, 072, 120, 180	A Canada/U.S.A.	Foundation Mica Accent
	<b>D120S</b>	Dual – 1 Power / 2 USB / 0 Data – Standard USB Capacity				
	<b>D200N</b>	Dual – Power Only				
	<b>Q202N</b>	Quad – 2 Power / 0 USB / 2 Data				
	<b>Q221H</b>	Quad – 2 Power / 2 USB / 1 Data – High USB Capacity				
	<b>Q221S</b>	Quad – 2 Power / 2 USB / 1 Data – Standard USB Capacity				
	<b>Q240S</b>	Quad – 2 Power / 4 USB / 0 Data – Standard USB Capacity				
	<b>Q320H</b>	Quad – 3 Power / 2 USB / 0 Data – High USB Capacity				
	<b>Q320S</b>	Quad – 3 Power / 2 USB / 0 Data – Standard USB Capacity				

## SAMPLE ORDER CODE

BEEPC A	D101N	Q	120	A	52
---------	-------	---	-----	---	----

DIMENSIONS  
INCHES / MM

L
48 / 1219
72 / 1829
120 / 3048
180 / 4572

## PRICING

## PLUG-IN (A)

D101N	D120S	D200N	Q202N	Q221S	Q221H	Q240S	Q320S	Q320H
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
289	362	266	406	480	559	552	428	507
289	362	266	406	480	559	552	428	507
356	428	334	472	545	624	617	495	574

## IEC CONNECTOR (C)

D101N	D120S	D200N	Q202N	Q221S	Q221H	Q240S	Q320S	Q320H
289	362	266	406	480	n/a	552	428	n/a
289	362	266	406	480	n/a	552	428	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a