Xpress

This support comes with full infill and is an alternative to legs for Rectangular Worksurfaces (B_RWL or B_RWC) and Run-Off Worksurfaces (B_MHH, B_MPL $^{-}$ or B_MPG).

BWWF Frame Leg - Full Infill

WHAT'S INCLUDED

 $1\ frame\ leg\ with\ full\ infill,\ levelers,\ 1\ mounting\ bracket\ and\ hardware.$

NOTES

Cannot be used to support a glass top.


Base height is 29" from the finished floor to the top of the finished worksurface with a leveling range of 3".

Support brackets are finished in black.

The centered solid infill is 11/16" thick.

The centered glass infill is 4 mm thick.

Not all finishes and glass infill finishes are available as Xpress, Please see Xpress catalogue and/or specification software for details.



PRODUCT OPTIONS

Infill Style	Height	Depth	Frame Leg Finish	Infill Finish
G Glass Infill L Solid Infill	S Standard (29")	24, 30, 36	AC Clear Anodized Foundation Mica	Glass Infill: Standard: FT Frosted Back-Painted Solid Infill: Source Laminate Flintwood (No Cathedral)

SAMPLE ORDER CODE

BWWF 1	. s	24	AC	XS
--------	-----	----	----	----

DIMENSIONS **INCHES / MM**

PRICING

SOLID INFILL (L)				
D	Source Laminate	Flintwood		
24 / 610	609	1037		
30 / 762	658	1155		
36 / 914	710	1353		

GLASS INFILL (G)			
Frosted Glass (FT)/ Back-Painted Glass			
781			
879			
954			