
lighting, electrics & communications



JNEPCF Ceiling Feed



The Ceiling Feed includes a junction box to connect to the building supply and routes power into the workstation from the ceiling.

WHAT'S INCLUDED

1 ceiling feed, 1 junction box and mounting hardware.

WHAT'S EXCLUDED

i-Connector and Four-Way Splitter.

Can be routed from the ceiling to the Power Box (JNEPB) through a Power Pole (JNEWPP).

The connection in the junction box and to the building power supply must be executed by a qualified electrician.

Check local codes for limits or restrictions on harness length.

Refer to Application Guide for applications.

PRODUCT OPTIONS

Wire System	Height (Power Pole)	Country of Installation	PVC Option
7K 7-Wire Dual Non Isolated	096, 120, 144	A Canada/U.S.A.	S Standard
7T 7-Wire Non Isolated Ground			V PVC Free
8K 8-Wire Dual Isolated			
8T 8-Wire Isolated Ground			

SAMPLE ORDER CODE

JNEPCF 8T	120	A	S
-----------	-----	---	---

DIMENSIONS INCHES / MM

PRICING

Н	
96 / 2438	_
120 / 3048	_
144 / 3658	

STANDARD (S)		
7T or 8T	7K or 8K	
307	323	
341	359	
376	394	

PVC FREE (V)		
7T or 8T	7K or 8K	
338	356	
409	429	
419	434	