

The Linear Power Module provides quick power, data, USB and accessibility in both sides.

WHAT'S INCLUDED

1 linear power module and mounting hardware.

WHAT'S EXCLUDED

Faceplate (JNECFK) and Cable Retractor Mechanism.

NOTES

Each USB Outlet has one USB-A port and one USB-C port for charging only.

The USB-A port always supplies 10 Watts maximum at 5 Volts DC when used alone.

The USB-C port supplies 18 Watts maximum at 5 to 12 Volts DC when used alone.


Maximum combined output is 15 Watts when both ports are used together: 5 Watts for USB-A port and 10 Watts for USB-C port.

The outlets are finished in Soft Gris.

Refer to local electrical code for guidance.

Not all configurations apply to all worksurface types. Refer to the Application Guide for details.

JNETLP Linear Power Module



Compact 8"
Configuration
(C0220 or C0300)

PRODUCT OPTIONS

Configuration	Wire System	Cord Length	Door and Case Finish	Frame Finish
C0220 Compact 8" – 2 Power/2 USB/0 Media	P Plug-In	072, 180	Foundation Mica	Foundation
C0300 Compact 8" – 3 Power/0 USB/0 Media				Accent Mica

SAMPLE ORDER CODE

JNETLP C0220	P	072	Q	Q
---------------------	----------	------------	----------	----------

DIMENSIONS INCHES / MM

L
72 / 1829
180 / 4572

PRICING

PLUG-IN (P)

CONFIGURATION

C0220	C0300
544	430
602	487