

The Split Base Feed delivers power from the floor to the Height-Adjustable Bench. It is wired to the building power supply in two places for New York City wiring restrictions.

H A B E B F S Split Base Feed

WHAT'S INCLUDED

1 base feed harness, junction box, I-connector and attachment hardware. (1 base feed module cover is included when End Condition (E) Style is selected).

NOTES

In the End Condition (E), the Split Base Feed module is mounted in a specified location within the Cable Channel. The Cable Channel is non-handed to support either left or right side mounting.


In the End Condition (E), the Split Base Feed can directly connect to the Power Module when I-Connector is removed, an additional Power Harness is not required to make this connection.

In the Mid Condition (M), the Split Base Feed module mounts to the Frame Link using an additional bracket (included). A 48" Power Harness is required to connect to the Power Module in the cable Channel.

The base feed module cover conceals the Base Feed module when it is mounted in the end condition within the Cable Channel.

Cable Channel Provision must be specified to allow the Power Harness to pass-thru and connect the Base Feed to the Power Module.

Available in 8-Wire Isolated Ground (8T), 7-Wire Non Isolated Ground (7T), 8-Wire Dual Ground (8K) and 7-Wire Dual Non Isolated (7K).



PRODUCT OPTIONS

Wire System	Length	Style	PVC Option	Country of Installation
8T 8-Wire Isolated Ground	018, 072	E End Condition	Standard	A Canada/USA
8K 8-Wire Dual Isolated		M Mid Condition	V PVC Free	
7T 7-Wire Non Isolated Ground				
7K 7-Wire Dual Non Isolated				

SAMPLE ORDER CODE

HABEBFS 8K	072	M	V	A
-------------------	------------	----------	----------	----------

DIMENSIONS INCHES / MM

L
18 / 457
72 / 1829

PRICING

ISOLATED GROUND (8T)			
End Condition		Mid Condition	
Standard	PVC Free	Standard	PVC Free
278	306	320	348
330	364	372	395

DUAL ISOLATED (8K)			
End Condition		Mid Condition	
Standard	PVC Free	Standard	PVC Free
354	389	395	431
406	447	447	489

NON ISOLATED GROUND (7T)			
End Condition		Mid Condition	
Standard	PVC Free	Standard	PVC Free
278	306	320	348
330	364	372	395

DUAL NON ISOLATED (7K)			
End Condition		Mid Condition	
Standard	PVC Free	Standard	PVC Free
354	389	395	431
406	447	447	489