


WWERO  
Receptacle Outlet



The Receptacle Outlet mounts onto the Power Module to provide access to power.

**WHAT'S INCLUDED**  
1 duplex.

**NOTES**  
Specified individually for maximum circuit flexibility.

Two receptacles can be mounted to each side of the Power Module (WWEPM).

Styles include Standard 15 amp, T-Slot 20 amp, USB, Controlled 15 and 20 amp.

Outlet configurations consist of Circuit 1, Circuit 2, Circuit 3 (use 7T and 8T only), Circuit 5 (8T and 8K only), Circuit 6 (use 8K only), Circuit A (7T and 7K only) and Circuit B (7K only).

Receptacle style D and E include a marking indicating it is connected to a control system.

Available in 15 amp and 20 amp.

PRODUCT OPTIONS

Receptacle Style	Outlet Configuration	Country of Installation	Receptacle Color
<b>S</b> Standard 15 Amp	<b>1</b> Circuit 1	<b>A</b> Canada/USA	<b>YY</b> Ebony
<b>T</b> T-Slot 20 Amp	<b>2</b> Circuit 2		<b>YF</b> Storm White
<b>D</b> Controlled 15 Amp	<b>3</b> Circuit 3 (Use with 7T & 8T only)		<b>YN</b> Platinum Grey Coordinate
<b>E</b> Controlled 20 Amp	<b>5</b> Circuit 5 (use with 8T & 8K only)		<b>YV</b> Very White Coordinate
	<b>6</b> Circuit 6 (Use with 8K only)		
	<b>A</b> Non Isolated Ground Circuit (use with 7T & 7K only)		
	<b>B</b> Non Isolated Ground Circuit (use with 7K only)		

SAMPLE ORDER CODE

WWERO S	6	A	YF
---------	---	---	----

RECEPTACLE STYLE	PRICING
S	44
T	53
D	44
E	53