


Xpress

E K R O  
Receptacle Outlet



The Receptacle Outlet mounts onto the Power Module to provide access to power.

**WHAT'S INCLUDED**  
1 duplex.

**NOTES**  
Specified individually for maximum circuit flexibility.

Styles include Standard 15 amp, T-Slot 20 amp, Controlled 15 and 20 amp.

Outlet configurations consist of Circuit 1, Circuit 2, Circuit 3 (use 7T and 8T only), Circuit 5 (8T and 8K only), Circuit 6 (use 8K only), Circuit A (7T and 7K only) and Circuit B (7K only).

Receptacle style D and E include a marking indicating it is connected to a control system.

**Xpress** Available through *Teknion's Xpress Program*.

PRODUCT OPTIONS

Receptacle Style		Outlet Configuration (Single-Sided)	Country of Installation	Finish	
<b>S</b>	Standard 15 Amp	<b>1</b> Circuit 1	<b>A</b> Canada/U.S.A.	<b>YY</b>	Ebony
<b>T</b>	T-Slot 20 Amp	<b>2</b> Circuit 2		<b>YF</b>	Storm White
<b>D</b>	Controlled 15 Amp	<b>3</b> Circuit 3 (for use with 7T & 8T)		<b>YN</b>	Platinum Grey Coordinate
<b>E</b>	Controlled 20 Amp	<b>5</b> Circuit 5 (use with 8T & 8K only)		<b>YV</b>	Very White Coordinate
		<b>6</b> Circuit 6 (for use with 8K)			
		<b>A</b> Circuit A Non Isolated Ground (use with 7T & 7K only)			
		<b>B</b> Circuit B Non Isolated Ground (use with 7K only)			

SAMPLE ORDER CODE

<b>EKRO S</b>	<b>5</b>	<b>A</b>	<b>YF</b>
---------------	----------	----------	-----------

RECEPTACLE STYLE

S
T
D
E

PRICING

44
53
44
53