Xpress YEABAP

Above & Below Surface Access Power Box

Above and Below provides the same functionality as the integrated One Table One Plug System but does so externally. Each Above and Below accessory is hard-wired to the Below Power Box which has a single cord that connects to any outlet.

What's Included

Selected Surface Access Power Box connected to the Below Power Box, selected cord and plug type.

Notes

Linking cord covered in Grey Cloth.

Below Power Box contains five plugs, two duplexes on front face and one simplex on the end.

Below Power Box finished in Clear Anodized.

Duplexes finished in Grey, End Simplex finished in White.

Access grommet not included. Must be ordered separately.

USB-A port supplies 10 Watts (5VDC) when used in single port mode.

USB-C port supplies 18 Watts (5/9/12VDC) when used in single port mode.

USB-C port will support Quick Charge when used in single port mode.

When both ports are used at the same time, output may be reduced.

Xpress Available through Teknion's Xpress Program.



PRODUCT OPTIONS

	Application	Below Configuration	Surface Access Power Box Configuration	Linking Cord Length	Power Cord Length	(Cord & Plug Type
01	HAB - Center Access Door Cut Out	500 5 Power	T3001 Triple - 3 Power/ Data T2111 Triple - 2 Power/ 1 USB-A/		P072 Plug-in with 6 ft cord P120 Plug-in with 10 ft cord	A	Canada/USA Plug-in
			1 USB-C		P180 Plug-in with 15 ft cord		

SAMPLE ORDER CODE

YEABAP 01	500	T3001	4	P120	A

CONFIGURATION PRICING

	Plug-in with 6 ft Cord	Plug-in with 10 ft Cord	Plug-in with 15 ft Cord	
T3001	889	927	965	
T2111	988	1027	1064	