



Flush Power Module, Standard Plug-In

Power Module with the user interface flush to the table surface.

What's Included

Face plate and cable clip kit (four clips).

Notes


Compatible with 1" to 1.5" thick worksurfaces.

USB-A Output: 5VDC 2.1A on USB A (12 W).

USB-C Output: 5-12 VDC (18 W).

USB-C Output: 5-20 VDC 3.25A (65 W).

Cord is Grey cloth covered and PVC free.



Rectangular, Triple
(shown)

PRODUCT OPTIONS

Faceplate Style		Electrical Cut Out	Configuration	Cord Length	Country of Installation	Receptacle Finish	Faceplate Finish
C	Circular	AH Dual	AJ 1 Power / 1 USB A+C (65W)	072 72"	A Canada/USA	YA Atrium White Coordinate	Foundation
R	Rectangular	AJ Triple	AM 1 Power / 1 USB A+C (18W)	120 120"		YS Soft Gris Coordinate	Mica
T	Rectangular with Pass-Through		AS 2 Power	180 180"		YY Ebony Coordinate	Accent
			AZ 2 Power / 1 USB A+C (65W)				
			BA 2 Power / 1 USB A+C (18W)				
			BJ 3 Power				

SAMPLE ORDER CODE

YEFPA R	AJ	AZ	120	A	YY	52
----------------	-----------	-----------	------------	----------	-----------	-----------

DIMENSIONS INCHES / MM

Cord Length
72 / 1829
120 / 3048
180 / 4572

PRICING

CIRCULAR

	1 Power / 1 USB A+C (18W)	1 Power / 1 USB A+C (65W)
2 Power		
233	362	470
259	388	496
292	421	529

RECTANGULAR

DUAL CUT OUT

	1 Power / 1 USB A+C (18W)	1 Power / 1 USB A+C (65W)
2 Power		
233	362	470
259	388	496
292	421	529

TRIPLE CUT OUT

	2 Power / 1 USB A+C (18W)	2 Power / 1 USB A+C (65W)
3 Power		
276	379	488
302	405	514
335	438	547

RECTANGULAR WITH PASS-THROUGH

	1 Power / 1 USB A+C (18W)	1 Power / 1 USB A+C (65W)
2 Power		
242	371	479
268	397	505
301	430	538