


YQX **Xpress**

hiSpace Quick Connect Height-Adjustable Mechanism,
Round Legs



hiSpace Quick Connect Height-Adjustable Mechanism, Round Legs must be paired with Rectangular Height-Adjustable Worksurface with Connection Kit for hiSpace Quick Connect (WBX), Rectangular Height-Adjustable Worksurface with Radius Corners and Connection Kit for hiSpace Quick Connect (WJX) or Rectangular Height-Adjustable Worksurface with Routes Corners (WQX) to create a complete table solution

What's Included

1 pair of feet, 1 pair of leg columns, 1 power pak (includes 1 cable organizer with felt cover, preinstalled control box, 1 switch, 1 15' power cord, 2 motor cables)

Notes

Meets ANSI/BIFMA testing requirements.
BIFMA compliant height-adjustment range from 22 3/5" to 48 7/10" from the top of a 1" thick worksurface.
Includes a 240V universal control box.
Standby power consumption of 0.2W.
Option of 0.2W Power cord is 10' long.
This is not a complete Base Only product. The Connection Kit top frame is required and included on WBX, WJX and WQX.

Xpress Available through *Teknion's Xpress Program*.

PRODUCT OPTIONS

Base Mechanism	Actual Depth	Actual Width	Screen Frame Provision	Base Finish
9 Extended Electric (22-3/5"-48-7/10")	29, 30	46, 52, 58, 60, 64, 70, 72	N None 6 6" Frame Actual Width Reduction	52 Ebony 60 Platinum 83 Very White

SAMPLE ORDER CODE

YQX 9	30	60	6	52
--------------	-----------	-----------	----------	-----------

PRODUCT OPTIONS (CONTINUED)

Switch	Power Pack	Undersurface Cable Management	Vertical Wire Carrier
D Display with Up/Down Memory A Toggle Display with Memory	1 Cable Organizer with Felt Cover	N None 3 Dual Plastic Trays + Powerbar 4 Dual Plastic Trays	N None Y With Vertical Wire Carrier

SAMPLE ORDER CODE (CONTINUED)

D	1	4	Y
----------	----------	----------	----------

See Pricing on the following page.

Xpress YQX

hiSpace Quick Connect Height-Adjustable Mechanism, Round Legs (Continued)

PRICING

2049

If Dual Plastic Trays + Power Bar are specified, add 286

If Dual Plastic are specified, add 58

If Vertical Wire Carrier is specified, add 334