


YSX **Xpress**

hiSpace Quick Connect Height-Adjustable Freestanding Table Mechanism



hiSpace Quick Connect Height-Adjustable Freestanding Table Mechanism must be paired with Rectangular Height-Adjustable Worksurface with Connection Kit for hiSpace Quick Connect (WBX) or Rectangular Height-Adjustable Worksurface with Radius Corners and Connection Kit for hiSpace Quick Connect (WJX) to create a complete table solution.

What's Included

1 pair of feet, 1 pair of leg columns, 1 power pak (includes 1 cable organizer with felt cover, pre-installed control box, 1 switch, 1 15' power cord, 2 motor cables)

Notes

- Meets ANSI/BIFMA testing requirements
- BIFMA compliant height-adjustment range from 22 3/5" to 48 7/10" from the top of a 1" thick worksurface
- Includes a 240V universal control box
- Standby power consumption of 0.2W
- Power cord is 10' long
- This is not a complete Base Only product. The Connection Kit top frame is required and included on WBX and WJX.

**Xpress** Available through *Teknion's Xpress Program*.

PRODUCT OPTIONS

Base Mechanism	Surface Depth	Surface Width	Screen Frame Provision	Base Finish
<b>9</b> Extended Electric (22 3/5"-48 7/10")	23, 29	46, 52, 58, 64, 70, 76, 82	<b>N</b> None <b>6</b> 6" Frame Actual Width Reduction	<b>52</b> Ebony <b>60</b> Platinum <b>83</b> Very White

SAMPLE ORDER CODE

YSX 9	29	58	6	52
-------	----	----	---	----

PRODUCT OPTIONS (CONTINUED)

Switch	Power Pak	Undersurface Cable Management	Vertical Wire Carrier
<b>D</b> Display with Up/Down Memory <b>A</b> Toggle Display with Memory	<b>1</b> Cable Organizer with Felt Cover	<b>N</b> None <b>3</b> Dual Plastic Trays + Powerbar <b>4</b> Dual Plastic Trays	<b>N</b> None <b>-C</b> With Vertical Wire Carrier <b>E</b> Ebony Coordinate <b>7</b> Platinum Coordinate <b>V</b> Very White Coordinate

SAMPLE ORDER CODE (CONTINUED)

D	1	4	E
---	---	---	---

See Pricing on the following page.

Xpress YSX

hiSpace Quick Connect Height-Adjustable Freestanding Table  
Mechanism (Continued)

PRICING

2049

If Dual Plastic Trays + Power Bar are specified, add 286  
If Dual Plastic are specified, add 58  
If Vertical Wire Carrier is specified, add 334