

# Height-Adjustment Range

The following chart outlines the weight capacity, adjustment range and power consumption for each height adjustable table mechanism.

	Weight Capacity	Maximum Height (A)	Maximum Height (B)	Adjustment Range (C)	Split Surface (if applicable)		Power Consumption (Moving from sit to stand)			
					Keyboard Support Height Range (D)	Keyboard Support Tilt Range (E)	Stand by Power	Worksurface Only (Assumes 30" x 60")	Work-surface + 200 lbs	
<b>Navigate Base Mechanisms (Heights when using 1" top)</b>										
(1X) Counterbalance Lower Edition (26"-43")	150 lbs*	43.5"	26.5"	16"	–	–	–	–	–	
(1S) Counterbalance Standard (29"-49")	150 lbs*	49.5"	29.5"	20"	–	–	–	–	–	
(7S) Standard Range Electric(27"-43")	200 lbs**	43"	27"	16"	–	–	0.1 W	150 W	250 W	
(9C)Extended Range Electric- Restricted Height (25"-48.7")	200 lbs**	48.7"	25"	23.7"	–	–	0.1 W	150 W	250 W	
(9E)Extended Range Electric- Extended Height (22.6"-48.7")	200 lbs**	48.7"	22.6"	26.1"	–	–	0.1 W	150 W	250 W	
<b>Navigate Complete tables</b>										
Height-Adjustable Extended Corner Complete Table	7S	300 lbs	43"	27"	16"	–	–	0.1W	150W	250W
	9E	300 lbs	48.7"	22.6"	26.1"					
Height-Adjustable Meeting Table (7S)	7S	200 lbs**	43"	27"	16"	–	–	0.1W	180W	250W
<b>Complements</b>										
Extended Electric Range (9)	250lbs	46"	21.5"	24.5"	13" (+6/-7)	30° (+/-15°)	0.1W	150W	250W	
Electric Standard Range (7)	250 lbs	43"	27"	16"	13" (+6/-7)	30° (+/-15°)	0.1W	150W	250W	
Top Surface Crank (5)	100 lbs	34"	22"	12"	13" (+6/-7)	30° (+/-15°)	–	–	–	
Increment (3)	350 lbs	34"	22"	12"	13" (+6/-7)	30° (+/-15°)	–	–	–	
Counter Balance (1)	150 lbs	45"	27"	18"	13" (+6/-7)	30° (+/-15°)	–	–	–	
<b>hiSpace</b>										
Extended Electric (9)	200 lbs	50.5"	25.5"	25"	–	–	4.5W	170W	310W	
Under Worksurface Crank (6)	120 lbs	34"	22"	12"	–	–	–	–	–	

\* Minus the weight of worksurface

\*\* Weight Capacity already includes the weight of the worksurface. Can be increased to 300 lbs via customer request (CR) process.

Note: Average time of a sit to stand adjustment is less than 10 seconds.

All electric table travel speeds are rated to 1.5/sec unless otherwise noted.