
Xpress

UNQBFSR Split Base Feed



The Split Base Feed is hard-wired to the building power supply in two places. It feeds power into the Panel. Typically required in New York.

WHAT'S INCLUDED

1 split base feed, liquid-tite cable (18" or 72"), 1 wiring junction box, mounting hardware and data/communication bezel.

Split Base Feed is finished in Platinum.

NOTES

Xpress Available through Teknion's Xpress Program.

PRODUCT OPTIONS

	Wire System	Length	Country of Installation	Bezel Finish	PVC Free
7T	7-Wire Non Isolated Ground	18, 72	A Canada/U.S.A.	YY Ebony YF Storm White	- Standard V PVC Free
7 K	7-Wire Dual Non Isolated			YN Platinum Grey	V IVC FIEE
8T	8-Wire Isolated Ground			Coordinate	
8K	8-Wire Dual Isolated				

SAMPLE ORDER CODE

UNQBFSR 8K 8K	72	YY	V
---------------	----	----	---

PRICING				
7-WIRE NON ISOLATED GROUND (7T) and 8-WIRE ISOLATED GROUND (8T)				
Standard	PVC Free (V)			
445	489			
513	564			
Standard	PVC Free (V)			
565	623			
648	715			
	7-WIRE NO Standard 445 513 7-WIRE DU. Standard 565	7-WIRE NON ISOLATED GROUND (7T) and 8-WIRE ISOLATED GROUND (8T) Standard PVC Free (V) 445 489 513 564 7-WIRE DUAL NON ISOLATED (7K) and 8-WIRE DUAL ISOLATED (8K) Standard PVC Free (V) 565 623		