


UNQBFSR Split Base Feed



The Split Base Feed is hard-wired to the building power supply in two places. It feeds power into the Panel. Typically required in New York.

WHAT'S INCLUDED

1 split base feed, liquid-tite cable (18" or 72"), 1 wiring junction box, mounting hardware and data/communication bezel.

Split Base Feed is finished in Platinum.

PRODUCT OPTIONS

Wire System	Length	Country of Installation	Bezel Finish	PVC Free
7T 7-Wire Non Isolated Ground	18, 72	A Canada/U.S.A.	YY Ebony	~ Standard
7K 7-Wire Dual Non Isolated			YF Storm White	V PVC Free
8T 8-Wire Isolated Ground			YN Platinum Grey Coordinate	
8K 8-Wire Dual Isolated				

SAMPLE ORDER CODE

UNQBFSR 8K	8K	72	YY	V
-------------------	-----------	-----------	-----------	----------

DIMENSIONS

L
18
72

PRICING

7-WIRE NON ISOLATED GROUND (7T) & 8-WIRE ISOLATED GROUND (8T)

Standard	PVC Free (V)
325	358
375	413

7-WIRE DUAL NON ISOLATED (7K) & 8-WIRE DUAL ISOLATED (8K)

Standard	PVC Free (V)
414	456
475	523