


# height-adjustability

**Xpress**

**Y G D**

## Navigate Height-Adjustable Built-in Base - Perpendicular Planning

One Table  
One Plug



Navigate Height-Adjustable Built-in Base - Perpendicular Planning is to be paired with Perpendicular Rectangular Height-Adjustable Built-in Worksurface, T-Legs, to create a District specific height-adjustable table supporting perpendicular planning.

### WHAT'S INCLUDED

1 Height-Adjustable base, leg and foot configuration as specified.

### NOTES

Electric base mechanism has 0.1 Watt resting power draw and uses 120V North American control box.

Vertical Wire Carrier includes cross channel bracket and mounts into credenza.

The height-adjustable worksurface must be specified separately.

For Switch details, see the *Application Guide* section.

Cross Channel Integrated Powerbar option (C) includes 3 outlets + 1 IEC Connection. This IEC connection accepts only one IEC-compatible power accessory (with an IEC cord terminal) at a time.

Undersurface cable management option (5) - Dual Plastic Trays + Powerbar with IEC refers to a Power Rod (with IEC cord terminal) that must be plugged into the IEC connection of the Cross Channel Integrated Powerbar option (C).

For more information about the One Table One Plug electrical system, IEC-compatible power accessories and planning with IEC Connection, refer to Complements: *Teknion's Ergonomics & Accessories Program*.

**Xpress** Available through *Teknion's Xpress Program*.

### PRODUCT OPTIONS

Leg Application	Base Mechanism	Actual Depth	Actual Width	Foot Style	Base Finish
<b>TSL</b> Left in Corridor, Right in Parallel Spine Credenza	<b>7S</b> Standard Electric (27" - 43")	30	65, 71, 77, 83	<b>1</b> Standard	Foundation Mica Accent
<b>TSR</b> Right in Corridor, Left in Parallel Spine Credenza					
<b>TCL</b> Left in Parallel Corridor Credenza, Right in alignment panel	<b>9C</b> Extended Electric-Restricted (25" - 48.7")				
<b>TCR</b> Right in Parallel Corridor Credenza, Left in alignment panel					
<b>TBL</b> Left in Parallel Corridor Credenza, Right in Parallel Spine Credenza					
<b>TBR</b> Right in Parallel Corridor Credenza, Left in Parallel Spine Credenza					

### SAMPLE ORDER CODE

<b>YGD TCL</b>	<b>9C</b>	<b>30</b>	<b>65</b>	<b>1</b>	<b>52</b>
----------------	-----------	-----------	-----------	----------	-----------

### PRODUCT OPTIONS (CONTINUED)

Switch Style	Switch Finish	Powerbar	Undersurface Cable Management	Vertical Wire Carrier (optional)
<b>S</b> Standard Up/Down	<b>E</b> Ebony Coordinate	<b>N</b> None	<b>N</b> None	<b>N</b> None
<b>D</b> Display with Up/Down Memory	<b>X</b> Anthracite	<b>I</b> Cross Channel Integrated - 4 Outlets	<b>1</b> Cable Organizer with Felt Cover	<b>E</b> Ebony Coordinate
<b>T</b> Toggle Up/Down	<b>7</b> Platinum		<b>3</b> Dual Plastic Trays+Powerbar	<b>7</b> Platinum Coordinate
<b>X</b> Display Toggle with Memory and Navigate GPS	<b>6</b> Crisp Grey	<b>C</b> Cross Channel Integrated - 3 Outlets + 1 IEC	<b>4</b> Dual Plastic Trays	<b>V</b> Very White Coordinate
			<b>5</b> Dual Plastic Trays+Powerbar with IEC	

### SAMPLE ORDER CODE (CONTINUED)

<b>X</b>	<b>X</b>	<b>I</b>	<b>1</b>	<b>E</b>
----------	----------	----------	----------	----------

See pricing in the following page.

**Navigate Height-Adjustable  
Built-in Base - Perpendicular  
Planning (Continued)**

**DIMENSIONS  
INCHES / MM**

D	W
30 / 762	65 / 1651
30 / 762	71 / 1803
30 / 762	77 / 1956
30 / 762	83 / 2108

**PRICING**

**STANDARD ELECTRIC**

Foundation	Mica/Accent
3262	3363
3262	3363
3262	3363
3262	3363

**EXTENDED ELECTRIC-RESTRICTED**

Foundation	Mica/Accent
3458	3560
3458	3560
3458	3560
3458	3560

- If Display with Up/Down Memory (D) switch is specified, add 177
- If Display Toggle with Memory and Navigate GPS (X) switch is specified, add 177
- If No Power Bar, Dual Plastic Trays are specified, add 57
- If No Power Bar, Dual Plastic Trays + Powerbar are specified, add 274
- If No Power Bar, Cable Organizer with Felt Cover is specified, add 281
- If Cross Channel Integrated Powerbar - 4 Outlets (I) or 3 Outlets + 1 IEC (C) with No Cable Management is specified, add 238
- If Cross Channel Integrated Powerbar - 4 Outlets (I) or 3 Outlets + 1 IEC (C) + Dual Plastic Trays are specified, add 296
- If Cross Channel Integrated Powerbar - 4 Outlets (I) + Dual Plastic Trays + Powerbar are specified, add 513
- If Cross Channel Integrated Powerbar - 3 Outlets + 1 IEC (C) + Dual Plastic Trays + Powerbar with IEC are specified, add 582
- If Cross Channel Integrated Powerbar - 4 Outlets (I) or 3 Outlets + 1 IEC (C) + Cable Organizer with Felt Cover are specified, add 521
- If Vertical Wire Carrier is specified, add 321