


# height-adjustability

**Xpress**

**Y G D**

## Navigate Height-Adjustable Built-in Base - Perpendicular Planning

One Table  
One Plug



Navigate Height-Adjustable Built-in Base - Perpendicular Planning is to be paired with Perpendicular Rectangular Height-Adjustable Built-in Worksurface, T-Legs, to create a District specific height-adjustable table supporting perpendicular planning.

### WHAT'S INCLUDED

1 Height-Adjustable base, leg and foot configuration as specified.

### NOTES

Electric base mechanism has 0.1 Watt resting power draw and uses 120V North American control box.

Vertical Wire Carrier includes cross channel bracket and mounts into credenza.

The height-adjustable worksurface must be specified separately.

For Switch details, see the *Application Guide* section.

Cross Channel Integrated Powerbar option (C) includes 3 outlets + 1 IEC Connection. This IEC connection accepts only one IEC-compatible power accessory (with an IEC cord terminal) at a time.

Undersurface cable management option (5) - Dual Plastic Trays + Powerbar with IEC refers to a Power Rod (with IEC cord terminal) that must be plugged into the IEC connection of the Cross Channel Integrated Powerbar option (C).

For more information about the One Table One Plug electrical system, IEC-compatible power accessories and planning with IEC Connection, refer to Complements: *Teknion's Ergonomics & Accessories Program*.

**Xpress** Available through *Teknion's Xpress Program*.

### PRODUCT OPTIONS

Leg Application	Base Mechanism	Actual Depth	Actual Width	Foot Style	Base Finish
<b>TSL</b> Left in Corridor, Right in Parallel Spine Credenza	<b>7S</b> Standard Electric (27" - 43") <b>9C</b> Extended Electric-Restricted (25" - 48.7")	30	65, 71, 77, 83	<b>1</b> Standard	Foundation Mica Accent
<b>TSR</b> Right in Corridor, Left in Parallel Spine Credenza					
<b>TCL</b> Left in Parallel Corridor Credenza, Right in alignment panel					
<b>TCR</b> Right in Parallel Corridor Credenza, Left in alignment panel					
<b>TBL</b> Left in Parallel Corridor Credenza, Right in Parallel Spine Credenza					
<b>TBR</b> Right in Parallel Corridor Credenza, Left in Parallel Spine Credenza					

### SAMPLE ORDER CODE

<b>YGD TCL</b>	<b>9C</b>	<b>30</b>	<b>65</b>	<b>1</b>	<b>52</b>
----------------	-----------	-----------	-----------	----------	-----------

### PRODUCT OPTIONS (CONTINUED)

Switch Style	Switch Finish	Powerbar	Undersurface Cable Management	Vertical Wire Carrier (optional)
<b>S</b> Standard Up/Down	<b>E</b> Ebony Coordinate	<b>N</b> None	<b>N</b> None	<b>N</b> None
<b>D</b> Display with Up/Down Memory	<b>X</b> Anthracite	<b>I</b> Cross Channel Integrated - 4 Outlets	<b>1</b> Cable Organizer with Felt Cover	<b>E</b> Ebony Coordinate
<b>T</b> Toggle Up/Down	<b>7</b> Platinum	<b>C</b> Cross Channel Integrated - 3 Outlets + 1 IEC	<b>3</b> Dual Plastic Trays+Powerbar	<b>7</b> Platinum Coordinate
<b>X</b> Display Toggle with Memory and Navigate GPS	<b>6</b> Crisp Grey		<b>4</b> Dual Plastic Trays	<b>V</b> Very White Coordinate
			<b>5</b> Dual Plastic Trays+Powerbar with IEC	

### SAMPLE ORDER CODE (CONTINUED)

<b>X</b>	<b>X</b>	<b>I</b>	<b>1</b>	<b>E</b>
----------	----------	----------	----------	----------

See pricing in the following page.

## Navigate Height-Adjustable Built-in Base - Perpendicular Planning (Continued)

### DIMENSIONS INCHES / MM

D	W
30 / 762	65 / 1651
30 / 762	71 / 1803
30 / 762	77 / 1956
30 / 762	83 / 2108

30 / 762	65 / 1651
30 / 762	71 / 1803
30 / 762	77 / 1956
30 / 762	83 / 2108

### PRICING

#### STANDARD ELECTRIC

Foundation	Mica/Accent
3389	3494
3389	3494
3389	3494
3389	3494

#### EXTENDED ELECTRIC-RESTRICTED

Foundation	Mica/Accent
3593	3699
3593	3699
3593	3699
3593	3699

If Display with Up/Down Memory (D) switch is specified, add 184

If Display Toggle with Memory and Navigate GPS (X) switch is specified, add 184

If No Power Bar, Dual Plastic Trays are specified, add 59

If No Power Bar, Dual Plastic Trays + Powerbar are specified, add 285

If No Power Bar, Cable Organizer with Felt Cover is specified, add 292

If Cross Channel Integrated Powerbar - 4 Outlets (I) or 3 Outlets + 1 IEC (C) with No Cable Management is specified, add 247

If Cross Channel Integrated Powerbar - 4 Outlets (I) or 3 Outlets + 1 IEC (C) + Dual Plastic Trays are specified, add 308

If Cross Channel Integrated Powerbar - 4 Outlets (I) + Dual Plastic Trays + Powerbar are specified, add 533

If Cross Channel Integrated Powerbar - 3 Outlets + 1 IEC (C) + Dual Plastic Trays + Powerbar with IEC are specified, add 605

If Cross Channel Integrated Powerbar - 4 Outlets (I) or 3 Outlets + 1 IEC (C) + Cable Organizer with Felt Cover are specified, add 541

If Vertical Wire Carrier is specified, add 334