


## Y G D

### Navigate Height-Adjustable Built-in Base - Perpendicular Planning

One Table  
One Plug



Navigate Height-Adjustable Built-in Base - Perpendicular Planning is to be paired with Perpendicular Rectangular Height-Adjustable Built-in Worksurface, T-Legs, to create a District specific height-adjustable table supporting perpendicular planning.

#### WHAT'S INCLUDED

1 Height-Adjustable base, leg and foot configuration as specified.

#### NOTES

Electric base mechanism has 0.1 Watt resting power draw and uses 120V North American control box.

Vertical Wire Carrier includes cross channel bracket and mounts into credenza.

The height-adjustable worksurface must be specified separately.

For Switch details, see the *Application Guide* section.

Cross Channel Integrated Powerbar option (C) includes 3 outlets + 1 IEC Connection. This IEC connection accepts only one IEC-compatible power accessory (with an IEC cord terminal) at a time.

Undersurface cable management option (5) - Dual Plastic Trays + Powerbar with IEC refers to a Power Rod (with IEC cord terminal) that must be plugged into the IEC connection of the Cross Channel Integrated Powerbar option (C).

For more information about the One Table One Plug electrical system, IEC-compatible power accessories and planning with IEC Connection, refer to Complements: *Teknion's Ergonomics & Accessories Program*.

#### PRODUCT OPTIONS

Leg Application	Base Mechanism	Actual Depth	Actual Width	Foot Style	Base Finish
<b>TSL</b> Left in Corridor, Right in Parallel Spine Credenza	<b>7S</b> Standard Electric (27" - 43")	30	65, 71, 77, 83	<b>1</b> Standard	Foundation Mica Accent
<b>TSR</b> Right in Corridor, Left in Parallel Spine Credenza					
<b>TCL</b> Left in Parallel Corridor Credenza, Right in alignment panel	<b>9C</b> Extended Electric-Restricted (25" - 48.7")				
<b>TCR</b> Right in Parallel Corridor Credenza, Left in alignment panel					
<b>TBL</b> Left in Parallel Corridor Credenza, Right in Parallel Spine Credenza					
<b>TBR</b> Right in Parallel Corridor Credenza, Left in Parallel Spine Credenza					

#### SAMPLE ORDER CODE

<b>YGD TCL</b>	<b>9C</b>	<b>30</b>	<b>65</b>	<b>1</b>	<b>52</b>
----------------	-----------	-----------	-----------	----------	-----------

#### PRODUCT OPTIONS (CONTINUED)

Switch Style	Switch Finish	Powerbar	Undersurface Cable Management	Vertical Wire Carrier (optional)
<b>S</b> Standard Up/Down	<b>E</b> Ebony Coordinate	<b>N</b> None	<b>N</b> None	<b>N</b> None
<b>D</b> Display with Up/Down Memory	<b>X</b> Anthracite	<b>I</b> Cross Channel Integrated - 4 Outlets	<b>1</b> Cable Organizer with Felt Cover	<b>E</b> Ebony Coordinate
<b>T</b> Toggle Up/Down	<b>7</b> Platinum	<b>C</b> Cross Channel Integrated - 3 Outlets + 1 IEC	<b>3</b> Dual Plastic Trays+Powerbar	<b>7</b> Platinum Coordinate
<b>X</b> Display Toggle with Memory and Navigate GPS	<b>6</b> Crisp Grey		<b>4</b> Dual Plastic Trays	<b>V</b> Very White Coordinate
			<b>5</b> Dual Plastic Trays+Powerbar with IEC	

#### SAMPLE ORDER CODE (CONTINUED)

<b>X</b>	<b>X</b>	<b>I</b>	<b>1</b>	<b>E</b>
----------	----------	----------	----------	----------

See pricing in the following page.

Y G D

**Navigate Height-Adjustable  
Built-in Base - Perpendicular  
Planning (Continued)**

**DIMENSIONS  
INCHES / MM**

D	W
30 / 762	65 / 1651
30 / 762	71 / 1803
30 / 762	77 / 1956
30 / 762	83 / 2108

**PRICING**

**STANDARD ELECTRIC**

Foundation	Mica/Accent
2812	2899
2812	2899
2812	2899
2812	2899

**EXTENDED ELECTRIC-RESTRICTED**

Foundation	Mica/Accent
2981	3069
2981	3069
2981	3069
2981	3069

- If Toggle Up/Down (T) switch is specified, add 70
- If Display with Up/Down Memory (D) switch is specified, add 153
- If Display Toggle with Memory and Navigate GPS (X) switch is specified, add 191
- If No Power Bar, Dual Plastic Trays are specified, add 49
- If No Power Bar, Dual Plastic Trays + Powerbar are specified, add 236
- If No Power Bar, Cable Organizer with Felt Cover is specified, add 242
- If Cross Channel Integrated Powerbar - 4 Outlets (I) or 3 Outlets + 1 IEC (C) with No Cable Management is specified, add 205
- If Cross Channel Integrated Powerbar - 4 Outlets (I) or 3 Outlets + 1 IEC (C) + Dual Plastic Trays are specified, add 255
- If Cross Channel Integrated Powerbar - 4 Outlets (I) + Dual Plastic Trays + Powerbar are specified, add 442
- If Cross Channel Integrated Powerbar - 3 Outlets + 1 IEC (C) + Dual Plastic Trays + Powerbar with IEC are specified, add 502
- If Cross Channel Integrated Powerbar - 4 Outlets (I) or 3 Outlets + 1 IEC (C) + Cable Organizer with Felt Cover are specified, add 449
- If Vertical Wire Carrier is specified, add 277