


# height-adjustability

**Xpress**

**Y H D**

## Navigate Height-Adjustable Built-in Base - Parallel Planning

One Table  
One Plug



Navigate Height-Adjustable Built-in Base - Parallel Planning is to be paired with Parallel Rectangular Height-Adjustable Built-in Worksurface, T-Legs, to create a District specific integrated height-adjustable table supporting parallel planning.

### WHAT'S INCLUDED

1 Height-Adjustable base, leg and foot configuration as specified.

### NOTES

Electric base mechanism has 0.1 Watt resting power draw and uses 120V North American control box.

Vertical Wire Carrier includes cross channel bracket and mounts into credenza.

The height-adjustable worksurface must be specified separately.

For Switch details, see the *Application Guide* section.

Cross Channel Integrated Powerbar option (C) includes 3 outlets + 1 IEC Connection. This IEC connection accepts only one IEC-compatible power accessory (with an IEC cord terminal) at a time.

Undersurface cable management option (5) - Dual Plastic Trays + Powerbar with IEC refers to a Power Rod (with IEC cord terminal) that must be plugged into the IEC connection of the Cross Channel Integrated Powerbar option (C).

For more information about the One Table One Plug electrical system, IEC-compatible power accessories and planning with IEC Connection, refer to Complements: *Teknion's Ergonomics & Accessories Program*.

**Xpress** Available through *Teknion's Xpress Program*.

### PRODUCT OPTIONS

Leg Application	Base Mechanism	Actual Depth	Actual Width	Foot Style	Base Finish
<b>TZL</b> Left in Perpendicular Credenza, Right toward Middle	<b>7S</b> Standard Electric (27" - 43")	29	52, 58, 64, 70, 76, 82	<b>1</b> Standard	Foundation
<b>TZR</b> Right in Perpendicular Credenza, Left toward Middle					Mica
<b>TDL</b> Left toward outside, Right in Shared Perpendicular Credenza	<b>9C</b> Extended Electric-Restricted (25" - 48.7")				Accent
<b>TDR</b> Right toward outside, Left in Shared Perpendicular Credenza					
<b>THL</b> Left in Perpendicular Credenza, Right in Shared Perpendicular Credenza					
<b>THR</b> Right in Perpendicular Credenza, Left in Shared Perpendicular Credenza					

### SAMPLE ORDER CODE

<b>YHD TZL</b>	<b>9C</b>	<b>29</b>	<b>58</b>	<b>1</b>	<b>52</b>
----------------	-----------	-----------	-----------	----------	-----------

### PRODUCT OPTIONS (CONTINUED)

Switch Style	Switch Finish	Powerbar	Undersurface Cable Management	Vertical Wire Carrier (optional)
<b>S</b> Standard Up/Down	<b>E</b> Ebony Coordinate	<b>N</b> None	<b>N</b> None	<b>N</b> None
<b>D</b> Display with Up/Down Memory	<b>X</b> Anthracite	<b>I</b> Cross Channel Integrated - 4 Outlets	<b>1</b> Cable Organizer with Felt Cover	<b>E</b> Ebony Coordinate
<b>T</b> Toggle Up/Down	<b>7</b> Platinum		<b>3</b> Dual Plastic Trays and Powerbar	<b>7</b> Platinum Coordinate
<b>X</b> Display Toggle with Memory and Navigate GPS	<b>6</b> Crisp Grey	<b>C</b> Cross Channel Integrated - 3 Outlets + 1 IEC	<b>4</b> Dual Plastic Trays	<b>V</b> Very White Coordinate
			<b>5</b> Dual Plastic Trays+Powerbar with IEC	

### SAMPLE ORDER CODE (CONTINUED)

<b>X</b>	<b>X</b>	<b>I</b>	<b>1</b>	<b>E</b>
----------	----------	----------	----------	----------

See pricing in the following page.

## Navigate Height-Adjustable Built-in Base - Parallel Planning (Continued)

### DIMENSIONS INCHES / MM

D	W
29 / 237	52 / 1321
29 / 237	58 / 1473
29 / 237	64 / 1626
29 / 237	70 / 1778
29 / 237	76 / 1930
29 / 237	82 / 2083

### PRICING

#### STANDARD ELECTRIC

Foundation	Mica/Accent
3352	3457
3352	3457
3389	3494
3389	3494
3389	3494
3389	3494

#### EXTENDED ELECTRIC-RESTRICTED

Foundation	Mica/Accent
3579	3684
3579	3684
3593	3699
3593	3699
3593	3699
3593	3699

If Display with Up/Down Memory (D) switch is specified, add 184

If Display Toggle with Memory and Navigate GPS (X) switch is specified, add 184

If No Power Bar, Dual Plastic Trays are specified, add 59

If No Power Bar, Dual Plastic Trays + Powerbar are specified, add 285

If No Power Bar, Cable Organizer with Felt Cover is specified, add 292

If Cross Channel Integrated Powerbar - 4 Outlets (I) or 3 Outlets + 1 IEC (C) with No Cable Management is specified, add 247

If Cross Channel Integrated Powerbar - 4 Outlets (I) or 3 Outlets + 1 IEC (C) + Dual Plastic Trays are specified, add 308

If Cross Channel Integrated Powerbar - 4 Outlets (I) + Dual Plastic Trays + Powerbar are specified, add 533

If Cross Channel Integrated Powerbar - 3 Outlets + 1 IEC (C) + Dual Plastic Trays + Powerbar with IEC are specified, add 605

If Cross Channel Integrated Powerbar - 4 Outlets (I) or 3 Outlets + 1 IEC (C) + Cable Organizer with Felt Cover are specified, add 541

If Vertical Wire Carrier is specified, add 334