


## Y H D

### Navigate Height-Adjustable Built-in Base - Parallel Planning

One Table  
One Plug



Navigate Height-Adjustable Built-in Base - Parallel Planning is to be paired with Parallel Rectangular Height-Adjustable Built-in Worksurface, T-Legs, to create a District specific integrated height-adjustable table supporting parallel planning.

#### WHAT'S INCLUDED

1 Height-Adjustable base, leg and foot configuration as specified.

#### NOTES

Electric base mechanism has 0.1 Watt resting power draw and uses 120V North American control box.

Vertical Wire Carrier includes cross channel bracket and mounts into credenza.

The height-adjustable worksurface must be specified separately.

For Switch details, see the *Application Guide* section.

Cross Channel Integrated Powerbar option (C) includes 3 outlets + 1 IEC Connection. This IEC connection accepts only one IEC-compatible power accessory (with an IEC cord terminal) at a time.

Undersurface cable management option (5) - Dual Plastic Trays + Powerbar with IEC refers to a Power Rod (with IEC cord terminal) that must be plugged into the IEC connection of the Cross Channel Integrated Powerbar option (C).

For more information about the One Table One Plug electrical system, IEC-compatible power accessories and planning with IEC Connection, refer to Complements: *Teknion's Ergonomics & Accessories Program*.

#### PRODUCT OPTIONS

Leg Application	Base Mechanism	Actual Depth	Actual Width	Foot Style	Base Finish
<b>TZL</b> Left in Perpendicular Credenza, Right toward Middle	<b>7S</b> Standard Electric (27" - 43")	29	52, 58, 64, 70, 76, 82	<b>1</b> Standard	Foundation Mica Accent
<b>TZR</b> Right in Perpendicular Credenza, Left toward Middle					
<b>TDL</b> Left toward outside, Right in Shared Perpendicular Credenza	<b>9C</b> Extended Electric-Restricted (25" - 48.7")				
<b>TDR</b> Right toward outside, Left in Shared Perpendicular Credenza					
<b>THL</b> Left in Perpendicular Credenza, Right in Shared Perpendicular Credenza					
<b>THR</b> Right in Perpendicular Credenza, Left in Shared Perpendicular Credenza					

#### SAMPLE ORDER CODE

<b>YHD TZL</b>	<b>9C</b>	<b>29</b>	<b>58</b>	<b>1</b>	<b>52</b>
----------------	-----------	-----------	-----------	----------	-----------

#### PRODUCT OPTIONS (CONTINUED)

Switch Style	Switch Finish	Powerbar	Undersurface Cable Management	Vertical Wire Carrier (optional)
<b>S</b> Standard Up/Down	<b>E</b> Ebony Coordinate	<b>N</b> None	<b>N</b> None	<b>N</b> None
<b>D</b> Display with Up/Down Memory	<b>X</b> Anthracite	<b>I</b> Cross Channel Integrated - 4 Outlets	<b>1</b> Cable Organizer with Felt Cover	<b>E</b> Ebony Coordinate
<b>T</b> Toggle Up/Down	<b>7</b> Platinum	<b>C</b> Cross Channel Integrated - 3 Outlets + 1 IEC	<b>3</b> Dual Plastic Trays and Powerbar	<b>7</b> Platinum Coordinate
<b>X</b> Display Toggle with Memory and Navigate GPS	<b>6</b> Crisp Grey		<b>4</b> Dual Plastic Trays	<b>V</b> Very White Coordinate
			<b>5</b> Dual Plastic Trays+Powerbar with IEC	

#### SAMPLE ORDER CODE (CONTINUED)

<b>X</b>	<b>X</b>	<b>I</b>	<b>1</b>	<b>E</b>
----------	----------	----------	----------	----------

See pricing in the following page.

YHD

**Navigate Height-Adjustable  
Built-in Base - Parallel Planning  
(Continued)**

**DIMENSIONS  
INCHES / MM**

D	W
29 / 237	52 / 1321
29 / 237	58 / 1473
29 / 237	64 / 1626
29 / 237	70 / 1778
29 / 237	76 / 1930
29 / 237	82 / 2083

**PRICING**

**STANDARD ELECTRIC**

Foundation	Mica/Accent
2781	2868
2781	2868
2812	2899
2812	2899
2812	2899
2812	2899

**EXTENDED ELECTRIC-RESTRICTED**

Foundation	Mica/Accent
2970	3057
2970	3057
2981	3069
2981	3069
2981	3069
2981	3069

- If Toggle Up/Down (T) switch is specified, add 70
- If Display with Up/Down Memory (D) switch is specified, add 153
- If Display Toggle with Memory and Navigate GPS (X) switch is specified, add 191
- If No Power Bar, Dual Plastic Trays are specified, add 49
- If No Power Bar, Dual Plastic Trays + Powerbar are specified, add 236
- If No Power Bar, Cable Organizer with Felt Cover is specified, add 242
- If Cross Channel Integrated Powerbar - 4 Outlets (I) or 3 Outlets + 1 IEC (C) with No Cable Management is specified, add 205
- If Cross Channel Integrated Powerbar - 4 Outlets (I) or 3 Outlets + 1 IEC (C) + Dual Plastic Trays are specified, add 255
- If Cross Channel Integrated Powerbar - 4 Outlets (I) + Dual Plastic Trays + Powerbar are specified, add 442
- If Cross Channel Integrated Powerbar - 3 Outlets + 1 IEC (C) + Dual Plastic Trays + Powerbar with IEC are specified, add 502
- If Cross Channel Integrated Powerbar - 4 Outlets (I) or 3 Outlets + 1 IEC (C) + Cable Organizer with Felt Cover are specified, add 449
- If Vertical Wire Carrier is specified, add 277