


## YSB

### hiSpace Quick Connect Parallelogram Height-Adjustable Freestanding Table Mechanism for District Power Spine



hiSpace Quick Connect Height-Adjustable Freestanding Parallelogram Table Mechanism must be paired with Parallelogram Height-Adjustable Worksurface with Connection Kit for District Power Spine(WBP) to create a complete table solution.

#### WHAT'S INCLUDED

1 pair of feet, 1 pair of leg columns, 1 power pak (includes 1 cable organizer with felt cover, pre-installed control box, 1 switch, 1 15' power cord, 2 motor cables).

#### WHAT'S EXCLUDED

This is not a complete Base Only product. The Connection Kit top frame is required and included on WBP.

#### NOTES

Meets ANSI/BIFMA testing requirements.

BIFMA compliant height-adjustment range from 22.6" to 48.7" from the top of a 1" thick worksurface.

Includes a 240V universal control box. Standby power consumption of 0.2W.

Power cord is 15' long.

#### PRODUCT OPTIONS

Base Mechanism	Surface Depth	Surface Width	Handedness	Base Finish
<b>9E</b> Extended Electric (22.6" - 48.7")	23, 29	60, 72	<b>C</b> Spine Front & Centered for Parallel <b>L</b> Left Hand <b>R</b> Right Hand	<b>52</b> Ebony <b>60</b> Platinum <b>83</b> Very White

#### SAMPLE ORDER CODE

<b>YSB 9E</b>	<b>29</b>	<b>72</b>	<b>R</b>	<b>52</b>
---------------	-----------	-----------	----------	-----------

#### PRODUCT OPTIONS (CONTINUED)

Switch	Power Pak	Undersurface Cable Management	Vertical Wire Carrier	Vertical Wire Carrier Finish
<b>D</b> Display with Up/Down Memory	<b>N</b> None <b>1</b> Cable Organizer with Felt Cover	<b>N</b> None <b>4</b> Dual Plastic Tray	<b>N</b> None <b>7</b> With Vertical Wire Carrier	<b>E</b> Ebony Coordinate <b>7</b> Platinum Coordinate <b>V</b> Very White Coordinate

#### SAMPLE ORDER CODE (CONTINUED)

<b>D</b>	<b>1</b>	<b>4</b>	<b>N</b>	<b>7</b>
----------	----------	----------	----------	----------

#### PRICING

No Power Pak	Power Pak Cable Organizer with Felt Cover
1700	1941

If Cable Management, Dual Plastic Tray (4) is specified, add 48

If Vertical Wire Carrier is specified, add 277