


height-adjustability

YVD

Navigate Height-Adjustable Built-in Gable Base - Perpendicular Planning

One Table
One Plug



Navigate Height-Adjustable Built-in Gable Base - Perpendicular Planning is to be paired with Perpendicular Rectangular Height-Adjustable Built-in Worksurface, Gable, to create a District specific height-adjustable table supporting perpendicular planning.

WHAT'S INCLUDED

1 Height-Adjustable base, leg and foot configuration as specified.

NOTES

Electric base mechanism has 0.1 Watt resting power draw and uses 120V North American control box.

E-Chain includes cross channel bracket and mounts into credenza.

The height-adjustable worksurface must be specified separately.

For Switch details, see the *Application Guide* section.

Cross Channel Integrated Powerbar option (C) includes 3 outlets + 1 IEC Connection. This IEC connection accepts only one IEC-compatible power accessory (with an IEC cord terminal) at a time.

Undersurface cable management option (5) - Dual Plastic Trays + Powerbar with IEC refers to a Power Rod (with IEC cord terminal) that must be plugged into the IEC connection of the Cross Channel Integrated Powerbar option (C).

For more information about the One Table One Plug electrical system, IEC-compatible power accessories and planning with IEC Connection, refer to Complements: *Teknion's Ergonomics & Accessories Program*.

PRODUCT OPTIONS

Leg Application	Base Mechanism	Actual Depth	Actual Width	Base Finish	Water Fall Finish
GSL Left Gable alignment Corridor, Right in Parallel Spine Credenza	7S Standard Electric (27" - 43")	30	53, 59, 65, 71, 77, 83	Foundation	Foundation
GSR Right Gable alignment Corridor, Left in Parallel Spine Credenza	9C Extended Electric-Restricted (25" - 48.7")			Mica Accent	Flintwood Natural Veneer

SAMPLE ORDER CODE

YVD GSL	9C	30	53	52	VZ
----------------	-----------	-----------	-----------	-----------	-----------

PRODUCT OPTIONS (CONTINUED)

Switch Style	Switch Finish	Powerbar	Undersurface Cable Management	E-Chain (optional)
S Standard Up/Down	E Ebony Coordinate	N None	N None	N None
D Display with Up/Down Memory	X Anthracite	I Cross Channel Integrated - 4 Outlets	1 Cable Organizer with Felt Cover	E Ebony Coordinate
T Toggle Up/Down	7 Platinum	C Cross Channel Integrated - 3 Outlets + 1 IEC	3 Dual Plastic Trays and Powerbar	7 Platinum Coordinate
X Display Toggle with Memory and Navigate GPS	6 Crisp Grey		4 Dual Plastic Trays	V Very White Coordinate
			5 Dual Plastic Trays+Powerbar with IEC	

SAMPLE ORDER CODE (CONTINUED)

X	X	I	1	E
----------	----------	----------	----------	----------

See pricing in the following page.

YVD

Navigate Height-Adjustable
Built-in Gable Base - Perpendicular
Planning (Continued)

DIMENSIONS
INCHES / MM

D	W
30 / 762	53 / 1346
30 / 762	59 / 1499
30 / 762	65 / 1651
30 / 762	71 / 1803
30 / 762	75 / 1905
30 / 762	83 / 2108

PRICING

STANDARD ELECTRIC

Foundation	Mica/Accent
3656	3733
3681	3758
3739	3816
3770	3847
3543	3620
3566	3643

EXTENDED ELECTRIC-RESTRICTED

Foundation	Mica/Accent
3947	4024
3974	4051
4004	4081
4036	4113
3813	3890
3838	3915

If Flintwood Water Fall Finish is specified,

53" Width	580
59" Width	638
65" Width	730
71" Width	789
75" Width	622
83" Width	680

If Natural Veneer Water Fall Finish is specified,

53" Width	632
59" Width	693
65" Width	789
71" Width	851
75" Width	689
83" Width	750

If Toggle Up/Down (T) switch is specified, add 61

If Display with Up/Down Memory (D) switch is specified, add 135

If Display Toggle with Memory and Navigate GPS (X) switch is specified, add 168

If Dual Plastic Trays are specified, add 43

If Dual Plastic Trays + Powerbar are specified, add 209

If Cable Organizer with Felt Cover is specified, add 213

If Cross Channel Integrated Powerbar - 4 Outlets (I) or 3 Outlets + 1 IEC (C) with No Cable Management is specified, add 181

If Cross Channel Integrated Powerbar - 4 Outlets (I) or 3 Outlets + 1 IEC (C) + Dual Plastic Trays are specified, add 225

If Cross Channel Integrated Powerbar - 4 Outlets (I) + Dual Plastic Trays + Powerbar are specified, add 390

If Cross Channel Integrated Powerbar - 3 Outlets + 1 IEC (C) + Dual Plastic Trays + Powerbar with IEC are specified, add 442

If Cross Channel Integrated Powerbar - 4 Outlets (I) or 3 Outlets + 1 IEC (C) + Cable Organizer with Felt Cover are specified, add 395

If E-Chain is specified, add 244