**Xpress**

Y V D

Navigate Height-Adjustable Built-in Gable Base - Perpendicular Planning

One Table
One Plug

Navigate Height-Adjustable Built-in Gable Base - Perpendicular Planning is to be paired with Perpendicular Rectangular Height-Adjustable Built-in Worksurface, Gable, to create a District specific height-adjustable table supporting perpendicular planning.

WHAT'S INCLUDED
1 Height-Adjustable base, leg and foot configuration as specified.

NOTES
Electric base mechanism has 0.1 Watt resting power draw and uses 120V North American control box.

Vertical Wire Carrier includes cross channel bracket and mounts into credenza.

The height-adjustable worksurface must be specified separately.

For Switch details, see the *Application Guide* section.

Cross Channel Integrated Powerbar option (C) includes 3 outlets + 1 IEC Connection. This IEC connection accepts only one IEC-compatible power accessory (with an IEC cord terminal) at a time.

Undersurface cable management option (5) - Dual Plastic Trays + Powerbar with IEC refers to a Power Rod (with IEC cord terminal) that must be plugged into the IEC connection of the Cross Channel Integrated Powerbar option (C).

For more information about the One Table One Plug electrical system, IEC-compatible power accessories and planning with IEC Connection, refer to *Complements: Teknion's Ergonomics & Accessories Program.*

Xpress Water Fall Finish Flintwood and Natural Veneer are excluded from *Teknion's Xpress Program.*

PRODUCT OPTIONS

Leg Application	Base Mechanism	Actual Depth	Actual Width	Base Finish	Water Fall Finish
GSL Left Gable alignment Corridor, Right in Parallel Spine Credenza	**7S** Standard Electric (27" - 43") **9C** Extended Electric-Restricted (25" - 48.7")	30	53, 59, 65, 71, 77, 83	Foundation Mica Accent	Foundation Flintwood Natural Veneer
GSR Right Gable alignment Corridor, Left in Parallel Spine Credenza					

SAMPLE ORDER CODE

YVD GSL	9C	30	53	52	VZ

PRODUCT OPTIONS (CONTINUED)

Switch Style	Switch Finish	Powerbar	Undersurface Cable Management	Vertical Wire Carrier (optional)
S Standard Up/Down	**E** Ebony Coordinate	**N** None	**N** None	**N** None
D Display with Up/Down Memory	**X** Anthracite	**I** Cross Channel Integrated - 4 Outlets	**1** Cable Organizer with Felt Cover	**E** Ebony Coordinate
T Toggle Up/Down	**7** Platinum	**C** Cross Channel Integrated - 3 Outlets + 1 IEC	**3** Dual Plastic Trays and Powerbar	**7** Platinum Coordinate
X Display Toggle with Memory and Navigate GPS	**6** Crisp Grey		**4** Dual Plastic Trays	**V** Very White Coordinate
			5 Dual Plastic Trays+Powerbar with IEC	

SAMPLE ORDER CODE (CONTINUED)

X	X	I	1	E

Y V D
Navigate Height-Adjustable
Built-in Gable Base - Perpendicular
Planning (Continued)

DIMENSIONS
INCHES / MM

PRICING

STANDARD ELECTRIC

D	W	Foundation	Mica/Accent
30 / 762	53 / 1346	4997	5103
30 / 762	59 / 1499	5031	5137
30 / 762	65 / 1651	5110	5215
30 / 762	71 / 1803	5152	5258
30 / 762	75 / 1905	5258	5364
30 / 762	83 / 2108	5311	5418

EXTENDED ELECTRIC-RESTRICTED

D	W	Foundation	Mica/Accent
30 / 762	53 / 1346	5394	5500
30 / 762	59 / 1499	5433	5537
30 / 762	65 / 1651	5515	5619
30 / 762	71 / 1803	5597	5665
30 / 762	75 / 1905	5707	5775
30 / 762	83 / 2108	5767	5832

If Flintwood Water Fall Finish is specified,

53" Width	793
59" Width	872
65" Width	997
71" Width	1082
75" Width	851
83" Width	929

If Natural Veneer Water Fall Finish is specified,

53" Width	863
59" Width	948
65" Width	1078
71" Width	1163
75" Width	942
83" Width	1024

If Display with Up/Down Memory (D) switch is specified, add 184

If Display Toggle with Memory and Navigate GPS (X) switch is specified, add 184

If No Power Bar, Dual Plastic Trays are specified, add 59

If No Power Bar, Dual Plastic Trays + Powerbar are specified, add 285

If No Power Bar, Cable Organizer with Felt Cover is specified, add 292

If Cross Channel Integrated Powerbar - 4 Outlets (I) or 3 Outlets + 1 IEC (C) with No Cable Management is specified, add 247

If Cross Channel Integrated Powerbar - 4 Outlets (I) or 3 Outlets + 1 IEC (C) + Dual Plastic Trays are specified, add 308

If Cross Channel Integrated Powerbar - 4 Outlets (I) + Dual Plastic Trays + Powerbar are specified, add 533

If Cross Channel Integrated Powerbar - 3 Outlets + 1 IEC (C) + Dual Plastic Trays + Powerbar with IEC are specified, add 605

If Cross Channel Integrated Powerbar - 4 Outlets (I) or 3 Outlets + 1 IEC (C) + Cable Organizer with Felt Cover are specified, add 541

If Vertical Wire Carrier is specified, add 334