


height-adjustability

YVD

Navigate Height-Adjustable Built-in Gable Base - Perpendicular Planning

One Table
One Plug



Navigate Height-Adjustable Built-in Gable Base - Perpendicular Planning is to be paired with Perpendicular Rectangular Height-Adjustable Built-in Worksurface, Gable, to create a District specific height-adjustable table supporting perpendicular planning.

WHAT'S INCLUDED

1 Height-Adjustable base, leg and foot configuration as specified.

NOTES

Electric base mechanism has 0.1 Watt resting power draw and uses 120V North American control box.

Vertical Wire Carrier includes cross channel bracket and mounts into credenza.

The height-adjustable worksurface must be specified separately.

For Switch details, see the *Application Guide* section.

Cross Channel Integrated Powerbar option (C) includes 3 outlets + 1 IEC Connection. This IEC connection accepts only one IEC-compatible power accessory (with an IEC cord terminal) at a time.

Undersurface cable management option (5) - Dual Plastic Trays + Powerbar with IEC refers to a Power Rod (with IEC cord terminal) that must be plugged into the IEC connection of the Cross Channel Integrated Powerbar option (C).

For more information about the One Table One Plug electrical system, IEC-compatible power accessories and planning with IEC Connection, refer to Complements: *Teknion's Ergonomics & Accessories Program*.

PRODUCT OPTIONS

Leg Application	Base Mechanism	Actual Depth	Actual Width	Base Finish	Water Fall Finish
GSL Left Gable alignment Corridor, Right in Parallel Spine Credenza	7S Standard Electric (27" - 43")	30	53, 59, 65, 71, 77, 83	Foundation	Foundation
GSR Right Gable alignment Corridor, Left in Parallel Spine Credenza	9C Extended Electric-Restricted (25" - 48.7")			Mica Accent	Flintwood Natural Veneer

SAMPLE ORDER CODE

YVD GSL	9C	30	53	52	VZ
----------------	-----------	-----------	-----------	-----------	-----------

PRODUCT OPTIONS (CONTINUED)

Switch Style	Switch Finish	Powerbar	Undersurface Cable Management	Vertical Wire Carrier (optional)
S Standard Up/Down	E Ebony Coordinate	N None	N None	N None
D Display with Up/Down Memory	X Anthracite	I Cross Channel Integrated - 4 Outlets	1 Cable Organizer with Felt Cover	E Ebony Coordinate
T Toggle Up/Down	7 Platinum	C Cross Channel Integrated - 3 Outlets + 1 IEC	3 Dual Plastic Trays and Powerbar	7 Platinum Coordinate
X Display Toggle with Memory and Navigate GPS	6 Crisp Grey		4 Dual Plastic Trays	V Very White Coordinate
			5 Dual Plastic Trays+Powerbar with IEC	

SAMPLE ORDER CODE (CONTINUED)

X	X	I	1	E
----------	----------	----------	----------	----------

See pricing in the following page.

**Navigate Height-Adjustable
Built-in Gable Base - Perpendicular
Planning (Continued)**

**DIMENSIONS
INCHES / MM**

D	W
30 / 762	53 / 1346
30 / 762	59 / 1499
30 / 762	65 / 1651
30 / 762	71 / 1803
30 / 762	75 / 1905
30 / 762	83 / 2108

30 / 762	53 / 1346
30 / 762	59 / 1499
30 / 762	65 / 1651
30 / 762	71 / 1803
30 / 762	75 / 1905
30 / 762	83 / 2108

PRICING

STANDARD ELECTRIC

Foundation	Mica/Accent
4146	4234
4174	4262
4240	4327
4275	4363
4017	4106
4043	4132

EXTENDED ELECTRIC-RESTRICTED

Foundation	Mica/Accent
4476	4564
4508	4594
4541	4628
4577	4665
4324	4412
4352	4440

If Flintwood Water Fall Finish is specified,

53" Width	658
59" Width	723
65" Width	828
71" Width	897
75" Width	706
83" Width	771

If Natural Veneer Water Fall Finish is specified,

53" Width	716
59" Width	786
65" Width	895
71" Width	965
75" Width	782
83" Width	850

If Toggle Up/Down (T) switch is specified, add 70

If Display with Up/Down Memory (D) switch is specified, add 153

If Display Toggle with Memory and Navigate GPS (X) switch is specified, add 191

If No Power Bar, Dual Plastic Trays are specified, add 49

If No Power Bar, Dual Plastic Trays + Powerbar are specified, add 236

If No Power Bar, Cable Organizer with Felt Cover is specified, add 242

If Cross Channel Integrated Powerbar - 4 Outlets (I) or 3 Outlets + 1 IEC (C) with No Cable Management is specified, add 205

If Cross Channel Integrated Powerbar - 4 Outlets (I) or 3 Outlets + 1 IEC (C) + Dual Plastic Trays are specified, add 255

If Cross Channel Integrated Powerbar - 4 Outlets (I) + Dual Plastic Trays + Powerbar are specified, add 442

If Cross Channel Integrated Powerbar - 3 Outlets + 1 IEC (C) + Dual Plastic Trays + Powerbar with IEC are specified, add 502

If Cross Channel Integrated Powerbar - 4 Outlets (I) or 3 Outlets + 1 IEC (C) + Cable Organizer with Felt Cover are specified, add 449

If Vertical Wire Carrier is specified, add 277