


height-adjustable credenzas

Z J H C

Height-Adjustable Credenza



Gable Support option
Right/End Application (R)
(shown)

WHAT'S INCLUDED

1 worksurface, height adjustable mechanism, height adjustable switch, worksurface grommet (if specified), standard integrated wire management includes wire looms, 1 Vertical Wire Carrier, four-outlet power bar, metal cable tray

NOTES

Knee Space for each depth is:

- 20" Depth = 11" space
- 24" Depth = 15" space
- 30" Depth = 21" space

Vertical Wire Carrier will have a central location.

Default HA Switch location will be on the right, but pilot holes will also allow a left location.

Height Adjustable Range is 27-1/2" to 48-1/2".

There is a 1" gap surrounding the worksurface to avoid pinch points.

Gable height will be 25".

Gable Support options Left, Right and None must be anchored to a storage unit on the side(s) without a gable.

Gable Support depth will match overall depth, except for the 30" overall depth. For the 30" overall, the Gable Depth will be 24".

PRODUCT OPTIONS

Grain Direction	Depth	Width (6" increments)	Gable Support	Finish	Grommet Style	Grommet Finish
H Horizontal	20, 24, 30	48 - 84	B Both/Modular Application L Left/End Application R Right/End Application N None/Center Application	Flintwood Veneer CWS Custom Wood Stain	N No Grommet	A Satin Nickel
V Vertical					A Rectangular Grommet Left	E Ebony
					B Rectangular Grommet Right	7 Platinum
					C Rectangular Grommet Centered	V Very White
					D Round Grommet Left	I Satin Nickel Coordinate
					E Round Grommet Right	X Anthracite
					F Round Grommet Centered	2 Burnished Bronze
						S Sepia Bronze
						M Graphite
						F Titanium Grey
						1 Gilded Ash

SAMPLE ORDER CODE

ZJHC V	24	78	N	VE	B	V
--------	----	----	---	----	---	---

See pricing on following page.

Z J H C
Height-Adjustable Credenza
(Continued)

DIMENSIONS
INCHES / MM

PRICING

D	W	BOTH/MODULAR APPLICATION		LEFT/RIGHT/END APPLICATION		NONE/MODULAR APPLICATION	
		Flintwood	Veneer	Flintwood	Veneer	Flintwood	Veneer
20 / 508	48 / 1219	9047	9198	8634	8766	8222	8337
20 / 508	54 / 1372	9185	9345	8773	8912	8358	8484
20 / 508	60 / 1524	9321	9491	8909	9060	8496	8629
20 / 508	66 / 1676	9544	9722	9132	9289	8717	8859
20 / 508	72 / 1829	9681	9868	9266	9437	8854	9004
20 / 508	78 / 1981	9986	10180	9573	9751	9162	9318
20 / 508	84 / 2134	10123	10327	9710	9896	9296	9466
24 / 610	48 / 1219	9223	9384	8767	8909	8315	8434
24 / 610	54 / 1372	9368	9538	8912	9062	8460	8587
24 / 610	60 / 1524	9512	9693	9057	9217	8605	8741
24 / 610	66 / 1676	9739	9930	9286	9454	8832	8980
24 / 610	72 / 1829	9884	10082	9431	9608	8975	9133
24 / 610	78 / 1981	10195	10403	9741	9928	9288	9452
24 / 610	84 / 2134	10340	10557	9886	10080	9433	9607
30 / 762	48 / 1219	9466	9644	8952	9105	8437	8560
30 / 762	54 / 1372	9619	9810	9107	9266	8590	8726
30 / 762	60 / 1524	9773	9973	9260	9432	8745	8888
30 / 762	66 / 1676	10013	10222	9497	9677	8983	9137
30 / 762	72 / 1829	10167	10384	9651	9843	9137	9300
30 / 762	78 / 1981	10489	10715	9974	10173	9460	9634
30 / 762	84 / 2134	10127	10337	10127	10337	9613	9796

If Rectangular Grommet, Painted is specified, add 219 for each grommet

If Rectangular Grommet, Satin Nickel (A) is specified, add 271 for each grommet

If Round Grommet, Ebony (E) is specified, add 160 for each grommet

If Round Grommet, Satin Nickel Coordinate (I) is specified, add 232 for each grommet