



BEEPC
Power Qube

One Table
One Plug



This product is mounted above a worksurface with Square Cut-Out and fixed inside Square Grommet Ring. It is used to provide quick power, data and USB access at the worksurface level.

WHAT'S INCLUDED

1 power qube, 1 twistable attachment ring and 1 square grommet ring.

NOTES

Must be installed in Square Grommet Ring.

Data Faceplate **not** included (if specified).

The Square Cut-Out mounting option can be specified on worksurface to allow Power Qube installation.

IEC Connector option (C) can only be used in combination with a Height-Adjustable Worksurfaces.

For more information about IEC Connector option (C), refer to One Table One Plug Application Guide in Complements: Teknion's Ergonomics & Accessories Programm. Simplex outlet finish to be Soft Gris.

Power Cord is a grey cloth covered type.

Each USB Outlet has one USB-A port and one USB-C port for charging only.

The USB-A port always supplies 10 Watts maximum at 5 Volts DC when used alone.

Standard USB-C Capacity (S):

The USB-C port supplies 18 Watts maximum at 5 to 12 Volts DC when used alone.

Maximum combined output is 15 Watts when both ports are used together: 5 Watts for USB-A port and 10 Watts for USB-C.

High USB-C Capacity (H):

The USB-C port supplies 65 Watts at 5 to 20 Volts DC when used alone.

Due to limitations with transformer design, the maximum combined output is 30 Watts when both ports are used together: 10 Watts for USB-A port and 20 Watts for USB-C port

This reduced output in dual port mode **will not** support charging of laptops or quick charging of some phones/tablets that require more than 5 Volts DC.

The USB-C port will charge laptops up to 65 Watts and support Quick Charge when used in single port mode.

PRODUCT OPTIONS

| Plug Type | Configuration | | Mounting Option | Power Cord Length (Inches) | Country of Installation | Case and Front Finish |
|------------------------------|---------------|---|---------------------------------------|----------------------------|-------------------------|------------------------|
| A Plug-In C IEC Connector | D101N | Dual – 1 Power / 0 USB / 1 Data | D Desk Edge Clamp Q Square Cut-Out | 048, 072, 120, 180 | A Canada/U.S.A. | Foundation Mica Accent |
| | D120S | Dual – 1 Power / 2 USB / 0 Data – Standard USB Capacity | | | | |
| | D200N | Dual – Power Only | | | | |
| | Q202N | Quad – 2 Power / 0 USB / 2 Data | | | | |
| | Q221H | Quad – 2 Power / 2 USB / 1 Data – High USB Capacity | | | | |
| | Q221S | Quad – 2 Power / 2 USB / 1 Data – Standard USB Capacity | | | | |
| | Q240S | Quad – 2 Power / 4 USB / 0 Data – Standard USB Capacity | | | | |
| | Q320H | Quad – 3 Power / 2 USB / 0 Data – High USB Capacity | | | | |
| | Q320S | Quad – 3 Power / 2 USB / 0 Data – Standard USB Capacity | | | | |

SAMPLE ORDER CODE

| | | | | | |
|---------|-------|---|-----|---|----|
| BEEPC A | D101N | Q | 120 | A | 52 |
|---------|-------|---|-----|---|----|

DIMENSIONS
INCHES / MM

| L |
|------------|
| 48 / 1219 |
| 72 / 1829 |
| 120 / 3048 |
| 180 / 4572 |

PRICING

| PLUG-IN (A) | | | | | | | | | |
|-------------------|-------|-------|-------|-------|-------|-------|-------|-------|-----|
| D101N | D120S | D200N | Q202N | Q221S | Q221H | Q240S | Q320S | Q320H | |
| n/a | n/a | n/a | n/a | n/a | n/a | n/a | n/a | n/a | n/a |
| 301 | 376 | 277 | 422 | 499 | 581 | 574 | 445 | 527 | |
| 301 | 376 | 277 | 422 | 499 | 581 | 574 | 445 | 527 | |
| 370 | 445 | 347 | 491 | 567 | 649 | 642 | 515 | 597 | |
| IEC CONNECTOR (C) | | | | | | | | | |
| D101N | D120S | D200N | Q202N | Q221S | Q221H | Q240S | Q320S | Q320H | |
| 301 | 376 | 277 | 422 | 499 | n/a | 574 | 445 | n/a | |
| 301 | 376 | 277 | 422 | 499 | n/a | 574 | 445 | n/a | |
| n/a | n/a | n/a | n/a | n/a | n/a | n/a | n/a | n/a | |
| n/a | n/a | n/a | n/a | n/a | n/a | n/a | n/a | n/a | |