


Xpress


BEEPC

Power Qube


One Table
One Plug



Connector and Cord Type



Plug-In (A)



IEC Connector (C)

This product is mounted above a worksurface with Square Cut-Out and fixed inside Square Grommet Ring. It is used to provide quick power, data and USB access at the worksurface level.

WHAT'S INCLUDED

1 power qube, 1 twistable attachment ring and 1 square grommet ring.

NOTES

Must be installed in Square Grommet Ring.

Data Faceplate **not** included (if specified).

The Square Cut-Out mounting option can be specified on worksurface to allow Power Qube installation.

IEC Connector option (C) can only be used in combination with a Height-Adjustable Worksurfaces.

For more information about IEC Connector option (C), refer to One Table One Plug Application Guide in Complements: Teknion's Ergonomics & Accessories Programm.

Power Cord is a grey cloth covered type.

Each USB Outlet has one USB-A port and one USB-C port for charging only.

The USB-A port always supplies 10 Watts maximum at 5 Volts DC when used alone.

Standard USB-C Capacity (S):

The USB-C port supplies 18 Watts maximum at 5 to 12 Volts DC when used alone.

Maximum combined output is 15 Watts when both ports are used together: 5 Watts for USB-A port and 10 Watts for USB-C.

High USB-C Capacity (H):

The USB-C port supplies 65 Watts at 5 to 20 Volts DC when used alone.

Due to limitations with transformer design, the maximum combined output is 30 Watts when both ports are used together: 10 Watts for USB-A port and 20 Watts for USB-C port

This reduced output in dual port mode **will not** support charging of laptops or quick charging of some phones/tablets that require more than 5 Volts DC.

The USB-C port will charge laptops up to 65 Watts and support Quick Charge when used in single port mode.

Not all finishes are available as Xpress, Please see Xpress catalogue and/or specification software for details.

PRODUCT OPTIONS

Plug Type	Configuration		Mounting Option	Power Cord Length (Inches)	Country of Installation	Case and Front Finish
A Plug-In	D101N	Dual – 1 Power / 0 USB / 1 Data	D Desk Edge Clamp Q Square Cut-Out	048, 072, 120, 180	A Canada/U.S.A.	Foundation Mica Accent
	D120S	Dual – 1 Power / 2 USB / 0 Data – Standard USB Capacity				
C IEC Connector	D200N	Dual – Power Only				
	Q202N	Quad – 2 Power / 0 USB / 2 Data				
	Q221H	Quad – 2 Power / 2 USB / 1 Data – High USB Capacity				
	Q221S	Quad – 2 Power / 2 USB / 1 Data – Standard USB Capacity				
	Q240S	Quad – 2 Power / 4 USB / 0 Data – Standard USB Capacity				
	Q320H	Quad – 3 Power / 2 USB / 0 Data – High USB Capacity				
	Q320S	Quad – 3 Power / 2 USB / 0 Data – Standard USB Capacity				

SAMPLE ORDER CODE

BEEPC A	D101N	Q	120	A	52
----------------	--------------	----------	------------	----------	-----------

DIMENSIONS INCHES / MM

L
48 / 1219
72 / 1829
120 / 3048
180 / 4572

PRICING

PLUG-IN (A)									
D101N	D120S	D200N	Q202N	Q221S	Q221H	Q240S	Q320S	Q320H	
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
278	348	256	391	462	462	531	412	412	
278	348	256	391	462	462	531	412	412	
343	412	321	454	601	525	594	552	476	

IEC CONNECTOR (C)									
D101N	D120S	D200N	Q202N	Q221S	Q221H	Q240S	Q320S	Q320H	
278	348	256	391	462	n/a	531	412	n/a	
278	348	256	391	462	n/a	531	412	n/a	
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	