


# multi-level workstations

**Xpress**

**BH\_RP**

## Height-Adjustable Peninsula – Bevel Post Leg

One Table  
One Plug



This Height-Adjustable Peninsula allows to work at seated and standing positions. It can be mounted on a Workwall Storage (BKKHW, BSMOBH, BSMHDP or BSMHCP) or a High or Low Secondary Desk (BH\_SB) at one end and is supported by a Bevel Post Leg at the other.

### WHAT'S INCLUDED

1 worksurface, 1 height-adjustable bevel base with levelers, 2 height-adjustable mechanism with supports and wire management, 1 power tray, 1 wire management kit, 1 switch for height-adjustable mechanism (as specified), 1 integrated powerbar (as specified), 1 rectangular cut-out with grommet (as specified), 1 square cut-out without ring (if applicable), and mounting hardware.

### WHAT'S EXCLUDED

Workwall Kneespace Module, Workwall Bookcase, Workwall Credenzas, High or Low Secondary Desk and Suspended Modesty Panel.

### NOTES

When Worksurface Thickness (V) option is specified, Radius (R) Corner Detail is **not** available.

When Worksurface Thickness (V) option is specified, only Edge Trim Style (F) option is available.

When Worksurface Thickness (M or X) option is specified, the Edge Trim Styles (6 or 9) options are available.

For more information about Integrated Powerbar with IEC Outlet option (P), refer to One Table One Plug Application Guide in Complements: Teknion's Ergonomics & Accessories Program.

The 1 9/16" (X) thickness is **not** available in all Source Laminate, Foundation Laminate and Edge Trim colors. Refer to the finish page of the Application Guide for details.

**Not all finishes** are available as Xpress, Please see Xpress catalogue and/or specification software for details.

### PRODUCT OPTIONS

Worksurface Thickness	Configuration	Depth	Width	Corner Detail	Grommet Option	Configuration	Powerbar	Range
<b>M</b> 1 3/16"	<b>K</b> Mid-Height	35	57, 63, 69, 75, 81, 87	<b>S</b> Straight (Shown)	<b>N</b> No Grommet (Shown)	<b>L</b> Left Handed (Shown)	<b>I</b> Integrated Powerbar	<b>E</b> Extended Range – 26" to 48" (Low or Mid)
<b>X</b> 1 9/16"	<b>H</b> High Secondary			<b>R</b> Radius	<b>O</b> Offset – Rectangular	<b>R</b> Right Handed	<b>N</b> None	
<b>V</b> 1 3/16" Knife Trim	<b>L</b> Low Secondary			<b>P</b> Offset – Rectangular & Square	<b>P</b> Integrated Powerbar with IEC Outlet	<b>E</b> Extended Range – 29" to 48" (High)		

### SAMPLE ORDER CODE

<b>BHMRP</b>	<b>L</b>	<b>35</b>	<b>87</b>	<b>S</b>	<b>P</b>	<b>L</b>	<b>N</b>	<b>E</b>
--------------	----------	-----------	-----------	----------	----------	----------	----------	----------

### PRODUCT OPTIONS CONTINUED

Switch	Worksurface Finish	Edge Trim Style	Edge Trim Finish	Base Finish	Grommet Finish (If Applicable)
<b>D</b> Display with Up/Down Memory	Foundation Laminate Flintwood (No Cathedral)	<b>6</b> Straight Trim	Edge Trim Colors (for trim style 6 or F)	Foundation	Foundation Mica
<b>F</b> Toggle Up/Down – Platinum		<b>9</b> Flintwood Flat Trim		Coordinate Colors	
<b>G</b> Toggle Up/Down – Crisp Grey		<b>F</b> Full Knife Trim			
<b>H</b> Toggle Up/Down – Anthracite					
<b>M</b> Display Toggle with Memory – Platinum					
<b>N</b> Display Toggle with Memory – Crisp Grey					
<b>O</b> Display Toggle with Memory – Anthracite					

### SAMPLE ORDER CODE CONTINUED

<b>D</b>	<b>2D</b>	<b>6</b>	<b>4D</b>	<b>74</b>	<b>74</b>
----------	-----------	----------	-----------	-----------	-----------

See Pricing on the following page.

**B H \_ R P**  
**Height-Adjustable Peninsula –**  
**Bevel Post Leg (Continued)**

**DIMENSIONS**  
**INCHES / MM**

**PRICING**

DIMENSIONS INCHES / MM		1 3/16" (M)		1 3/16" KNIFE EDGE (V)		1 9/16" (X)	
		Foundation Laminate	Flintwood	Foundation Laminate	Flintwood	Foundation Laminate	Flintwood
D	W						
35 / 889	57 / 1448	5263	6255	5388	n/a	5384	7080
35 / 889	63 / 1600	5314	6340	5449	n/a	5447	7157
35 / 889	69 / 1753	5365	6425	5510	n/a	5510	7234
35 / 889	75 / 1905	5416	6510	5571	n/a	5573	7311
35 / 889	81 / 2057	5458	6584	5623	n/a	5627	7429
35 / 889	87 / 2210	5509	6671	5684	n/a	5691	7525

If Switch Style (D, M, N or O) is specified, add 129.

If Powerbar (I or P) is specified, add 176.