
Xpress


BLEBP

Below Power Module


One Table One Plug



Cord and Plug Type



Standard Plug-In (A)



IEC Connector (C)

WHAT'S INCLUDED

1 below power module, HDMI Keystone Insert Atrium White or Ebony only (if specified), and mounting hardware.

NOTES

Not available in Chicago.

USB-A Output: 5VDC 2.1A on USB A (12 W).

USB-C Output: 5-12 VDC (18 W).

USB-C Output: 5-20 VDC 3.25A (65 W).

Cord is Grey cloth covered and PVC free.

IEC Connector option (C) can only be used in combination with a Height-Adjustable Worksurfaces.

For more information about IEC Connector option (C), refer to One Table One Plug Application Guide in Complements: Teknion's Ergonomics & Accessories Programm.

PRODUCT OPTIONS

Cord and Plug Type	Mounting Option	Configuration	Cord Length	Country of Installation	Receptacle Finish	Faceplate Finish	Bracket Finish
A Standard Plug-In **C** IEC Connector	**U** Standard Undermount	**RA** 1Power / 1USB – A+C (65W) / 1Rear Power **RB** 1Power / 1USB – A+C (18W) / 1Rear Power **RC** 2Power / 1Rear Power **RD** 1Power / 1HDMI / 1HDMI Rear Throughport	054, 072, 120, 180	**A** Canada / U.S.A.	**YA** Atrium White Coordinate **YS** Soft Gris Coordinate **YY** Ebony Coordinate	Foundation Mica Accent	Foundation Mica Accent

SAMPLE ORDER CODE

BLEBP A	U	RA	072	A	YY	52	52

DIMENSIONS
INCHES / MM

PRICING

STANDARD PLUG-IN (A)				
Cord Length	2Power / 1Rear Power (RC)	1Power / 1HDMI / 1 HDMI Rear Throughport (RD)	1Power / 1USB-A+C (18W) / 1 Rear Power (RB)	1Power / 1USB-A+C (65W) / 1 Rear Power (RA)
72 / 1829	214	259	297	378
120 / 3048	235	280	318	398
180 / 4572	259	304	342	422

IEC CONNECTOR (C)				
	2Power / 1Rear Power (RC)	1Power / 1HDMI / 1 HDMI Rear Throughport (RD)	1Power / 1USB-A+C (18W) / 1 Rear Power (RB)	1Power / 1USB-A+C (65W) / 1 Rear Power (RA)
54 / 1372	284	329	367	448
72 / 1829	294	339	377	458