Xpress

BLEFP
Flush Power Module

One Table One Plug

WHAT'S INCLUDED
1 flush power module and mounting hardware.

NOTES
Not available in Chicago.

USB-A Output: 5VDC 2.1A on USB A (12 W).

USB-C Output: 5-12 VDC (18 W)


USB-C Output: 5-20 VDC 3.25A (65 W).

Cord is Grey cloth covered and PVC free.


IEC Connector option (C) can only be used in combination with a Height-Adjustable Worksurfaces.

For more information about IEC Connector option (C), refer to One Table One Plug Application Guide in Complements: Teknion's Ergonomics & Accessories Programm.


Cord and Plug Type




Standard Plug-In (A)



IEC Connector (C)



Rectangular with Pass-Through (T)



Rectangular (R)

Triple (AJ)

PRODUCT OPTIONS

Cord and Plug Type	Faceplate Style	Electrical Cutout	Configuration	Cord Length	Country of Installation	Receptacle Finish	Faceplate Finish
A Standard Plug-In **C** IEC Connector	**R** Rectangular **T** Rectangular with Pass-Through	**AJ** Triple	**AJ** 1Power / 1USB – A+C (65W) **AM** 1Power / 1USB – A+C (18W) **AS** 2Power **AZ** 2Power / 1USB – A+C (65W) **BA** 2Power / 1USB – A+C (18W) **BJ** 3Power	054, 072, 120, 180	**A** Canada / U.S.A.	**YA** Atrium White Coordinate **YS** Soft Gris Coordinate **YY** Ebony Coordinate	Foundation Mica Accent

SAMPLE ORDER CODE

BLEFP A	R	AJ	AJ	072	A	YY	52

DIMENSIONS
INCHES / MM

PRICING

STANDARD PLUG-IN (A)

Cord Length	RECTANGULAR (R) TRIPLE (AJ) 3Power (BJ)	RECTANGULAR (R) TRIPLE (AJ) 2Power / 1USB-A+C (18W) (BA)	RECTANGULAR (R) TRIPLE (AJ) 2Power / 1USB-A+C (65W) (AZ)	RECTANGULAR WITH PASS-THROUGH (T) 2Power (AS)	RECTANGULAR WITH PASS-THROUGH (T) 1Power / 1USB-A+C (18W) (AM)	RECTANGULAR WITH PASS-THROUGH (T) 1Power / 1USB-A+C (65W) (AJ)
72 / 1829	207	284	365	175	270	353
120 / 3048	228	305	386	196	291	373
180 / 4572	252	329	410	219	315	397

IEC CONNECTOR (C)

	RECTANGULAR (R) TRIPLE (AJ) 3Power (BJ)	RECTANGULAR (R) TRIPLE (AJ) 2Power / 1USB-A+C (18W) (BA)	RECTANGULAR (R) TRIPLE (AJ) 2Power / 1USB-A+C (65W) (AZ)	RECTANGULAR WITH PASS-THROUGH (T) 2Power (AS)	RECTANGULAR WITH PASS-THROUGH (T) 1Power / 1USB-A+C (18W) (AM)	RECTANGULAR WITH PASS-THROUGH (T) 1Power / 1USB-A+C (65W) (AJ)
54 / 1372	277	354	435	245	340	423
72 / 1829	287	364	445	255	350	433