

The Linear Power Module provides accessibility of outlets and communication plugs in both sides.

**WHAT'S INCLUDED**

1 linear power module, media holder plate and mounting hardware.

**WHAT'S EXCLUDED**

Faceplate (BLECF).

**NOTES**

Each USB Outlet has one USB-A port and one USB-C port for charging only.

The USB-A port always supplies 10 Watts maximum at 5 Volts DC when used alone.

The USB-C port supplies 18 Watts maximum at 5 to 12 Volts DC when used alone.

Maximum combined output is 15 Watts when both ports are used together: 5 Watts for USB-A port and 10 Watts for USB-C port.

The faceplates (BLECF) **are not** compatible with Linear Power Module – Compact 8" (C0220 or C0300).

**Not** all configurations apply to all worksurface types. Refer to the Application Guide for details.


The outlets are finished in Soft Gris.

Refer to local electrical code for guidance.


**Not all configurations** are available as Xpress, Please see Xpress catalogue and/or specification software for details.

**PRODUCT OPTIONS**


Configuration	Wire System	Cord Length	Door and Case Finish	Frame Finish
<b>C0220</b> Compact 8" – 2 Power/2 USB/0 Media	<b>H</b> Hard Wire Base Feed (Single Circuit)	072, 180	Foundation	Foundation
<b>C0300</b> Compact 8" – 3 Power/0 USB/0 Media	<b>P</b> Plug-In (Shown)		Mica	Accent Mica
<b>S0442</b> Standard 18" – 4 Power/4 USB/2 Media				
<b>S0602</b> Standard 18" – 6 Power/0 USB/2 Media				
<b>X0882</b> Extended 28" – 8 Power/8 USB/2 Media				
<b>X1202</b> Extended 28" – 12 Power/0 USB/2 Media				



Extended 28"  
Configuration  
(X0882 or X1202)



Standard 18"  
Configuration  
(S0442 or S0602)



Compact 8"  
Configuration  
(C0220 or C0300)

**SAMPLE ORDER CODE**

<b>BLELP S0442</b>	<b>H</b>	<b>072</b>	<b>74</b>	<b>74</b>
--------------------	----------	------------	-----------	-----------

**DIMENSIONS**  
**INCHES / MM**

L
72 / 1829
180 / 4572

**PRICING**

**PLUG-IN (P)**

**CONFIGURATION**

C0220	C0300	S0442	S0602	X0882	X1202
534	422	815	594	1285	837
589	477	871	647	1338	894

Xpress

Xpress

Xpress

**HARD WIRE BASE FEED (H)**

S0442	S0602	X0882	X1202
984	760	1451	1004
n/a	n/a	n/a	n/a