
lighting, electrics & communications



JNEPCF Ceiling Feed



The Ceiling Feed includes a junction box to connect to the building supply and routes power into the workstation from the ceiling.

WHAT'S INCLUDED

1 ceiling feed, 1 junction box and mounting hardware.

WHAT'S EXCLUDED

i-Connector and Four-Way Splitter.

Can be routed from the ceiling to the Power Box (JNEPB) through a Power Pole (JNEWPP).

The connection in the junction box and to the building power supply must be executed by a qualified electrician.

Check local codes for limits or restrictions on harness length.

Refer to Application Guide for applications.

PRODUCT OPTIONS

| Wire System | Height (Power Pole) | Country of Installation | PVC Option |
|---|---------------------|-------------------------|------------|
| 7K 7-Wire Dual Non Isolated | 096, 120, 144 | A Canada/U.S.A. | S Standard |
| 7T 7-Wire Non Isolated Ground | | | V PVC Free |
| 8K 8-Wire Dual Isolated | | | |
| 8T 8-Wire Isolated Ground | | | |
| | | | |
| | | | |
| 7T 7-Wire Non Isolated Ground8K 8-Wire Dual Isolated | 0.70, 120, 111 | A Sanada C.S.A. | |

SAMPLE ORDER CODE

| JNEPCF 8T | 120 | A | S |
|-----------|-----|---|---|
|-----------|-----|---|---|

DIMENSIONS INCHES / MM

PRICING

| | STANDARI |
|------------|----------|
| Н | 7T or |
| 96 / 2438 | 30 |
| 120 / 3048 | 34 |
| 144 / 3658 | 37 |

| STANDARD (S) | | |
|--------------|----------|--|
| 7T or 8T | 7K or 8K | |
| 307 | 323 | |
| 341 | 359 | |
| 376 | 394 | |
| | | |

| PVC FREE (V) | | |
|--------------|----------|--|
| 7T or 8T | 7K or 8K | |
| 338 | 356 | |
| 409 | 429 | |
| 419 | 434 | |