The Linear Power Module provides quick power, data, USB and accessibility in both sides.

### WHAT'S INCLUDED

1 linear power module and mounting hardware.

## WHAT'S EXCLUDED

Faceplate (JNECFK) and Cable Rectractor Mechanism.

#### NOTES

Each USB Outlet has one USB-A port and one USB-C port for charging only.

The USB-A port always supplies 10 Watts maximum at 5 Volts DC when used alone.

The USB-C port supplies 18 Watts maximum at 5 to 12 Volts DC when used alone.

Maximum combined output is 15 Watts when both ports are used together: 5 Watts for USB-A port and 10 Watts for USB-C port.

The outlets are finished in Soft Gris.

Refer to local electrical code for guidance.

 $\mathbf{Not}$  all configurations apply to all worksurface types. Refer to the Application Guide for details.

# PRODUCT OPTIONS

	Configuration	Wire System	Cord Length	Door and Case Finish	Frame Finish
C0220	Compact 8" – 2 Power/2 USB/0 Media	P Plug-In	072, 180	Foundation	Foundation
	Compact 8" – 3 Power/0 USB/0 Media			Mica	Accent Mica


# SAMPLE ORDER CODE

	JNETLP C0220	Р	072	Q	Q
--	--------------	---	-----	---	---

#### DIMENSIONS INCHES / MM

PRICING

	PLUG-IN	I (P)	
	CONFIG	URATION	
L	C0220	C0300	
72 / 1829	544	430	
180 / 4572	602	487	



JNETLP

Linear Power Module

Compact 8" Configuration (C0220 or C0300)