

The Worksurface Power and Communication Center provides access to electrics and data at worksurface height.

WHAT'S INCLUDED

1 worksurface power and communication center, and mounting hardware.

WHAT'S EXCLUDED

Wire Management Clips, Structural Column and Voice/Data faceplates and jacks.

NOTES

The 3-Wire option (3P) has a flat 45° plug.


The data cut-out is designed to accept a data faceplate.

This product is finished in anodized aluminum with black top cap.

Cannot be mounted on a Spine Desk.

RLDCC
Worksurface Power and
Communication Center

Outlet Configurations	
Wiring Systems	Simplexes (from bottom)
3P	1111
4B	1122
5D	1123
7G	1255
8N	1255
8T	1235
8K	1256



PRODUCT OPTIONS

Wire System	Length	Country of Installation
3P 3-Wire (Plug In)	021, 024, 027, 030, 033, 036, 042, 048, 054, 060, 066, 072, 078, 084, 090, 096, 102, 108, 114, 120, 126, 132, 138, 144	A Canada / U.S.A.
4B 4-Wire		
5D 5-Wire		
7G 7-Wire, Isolated Ground		
8T 8-Wire, Isolated Ground		
8N 8-Wire, Separate Neutral		
8K 8-Wire, Dual Isolated		

SAMPLE ORDER CODE

RLDCC 4B	078	A
-----------------	------------	----------

DIMENSIONS
INCHES / MM

L
21 / 533
24 / 610
27 / 686
30 / 762
33 / 838
36 / 914
42 / 1067
48 / 1219
54 / 1372
60 / 1524
66 / 1676
72 / 1829
78 / 1981
84 / 2134
90 / 2286
96 / 2438
102 / 2591
108 / 2743
114 / 2896
120 / 3048
126 / 3200
132 / 3353
138 / 3505
144 / 3658

PRICING

3-Wire (3P)	4- or 5-Wire (4B or 5D)	7- to 8-Wire (7G to 8K)
n/a	216	222
n/a	219	225
n/a	222	227
n/a	225	232
n/a	227	235
n/a	232	239
n/a	237	244
n/a	241	249
n/a	248	253
n/a	252	258
n/a	256	263
210	262	268
n/a	267	275
n/a	271	280
n/a	278	284
n/a	283	289
n/a	288	293
244	292	297
n/a	296	304
n/a	303	309
n/a	307	314
n/a	312	319
n/a	318	324
275	321	328