

The Worksurface Power and Communication Center provides access to electrics and data at worksurface height.

## RLDCC

### Worksurface Power and Communication Center

#### WHAT'S INCLUDED

1 worksurface power and communication center, and mounting hardware.

#### WHAT'S EXCLUDED

Wire Management Clips, Structural Column and Voice/Data faceplates and jacks.

#### NOTES


The 3-Wire option (3P) has a flat 45° plug.

The data cut-out is designed to accept a data faceplate.

This product is finished in anodized aluminum with black top cap.

Cannot be mounted on a Spine Desk.

Outlet Configurations	
Wiring Systems	Simplexes (from bottom)
3P	1111
4B	1122
5D	1123
7G	1255
8N	1255
8T	1235
8K	1256



#### PRODUCT OPTIONS

Wire System	Length	Country of Installation
3P 3-Wire (Plug In)	021, 024, 027, 030, 033, 036, 042, 048, 054, 060, 066, 072, 078, 084, 090, 096, 102, 108, 114, 120, 126, 132, 138, 144	A Canada / U.S.A.
4B 4-Wire		
5D 5-Wire		
7G 7-Wire, Isolated Ground		
8T 8-Wire, Isolated Ground		
8N 8-Wire, Separate Neutral		
8K 8-Wire, Dual Isolated		

#### SAMPLE ORDER CODE

<b>RLDCC 4B</b>	<b>078</b>	<b>A</b>
-----------------	------------	----------

#### DIMENSIONS INCHES / MM

L
21 / 533
24 / 610
27 / 686
30 / 762
33 / 838
36 / 914
42 / 1067
48 / 1219
54 / 1372
60 / 1524
66 / 1676
72 / 1829
78 / 1981
84 / 2134
90 / 2286
96 / 2438
102 / 2591
108 / 2743
114 / 2896
120 / 3048
126 / 3200
132 / 3353
138 / 3505
144 / 3658

#### PRICING

3-Wire (3P)	4- or 5-Wire (4B or 5D)	7- to 8-Wire (7G to 8K)
n/a	167	171
n/a	169	174
n/a	171	176
n/a	174	180
n/a	176	183
n/a	180	186
n/a	184	189
n/a	188	193
n/a	192	196
n/a	195	200
n/a	199	205
189	204	208
n/a	207	213
n/a	211	216
n/a	215	220
n/a	219	224
n/a	223	228
213	227	231
n/a	230	236
n/a	235	239
n/a	238	244
n/a	242	248
n/a	247	252
236	250	255