

The Worksurface Power and Communication Center provides access to electrics and data at worksurface height.

WHAT'S INCLUDED

1 worksurface power and communication center, and mounting hardware.

WHAT'S EXCLUDED

Wire Management Clips, Structural Column and Voice/Data faceplates and jacks.

NOTES

The 3-Wire option (3P) has a flat 45° plug.


The data cut-out is designed to accept a data faceplate.

This product is finished in anodized aluminum with black top cap.

Cannot be mounted on a Spine Desk.

RLDCC
Worksurface Power and Communication Center

Outlet Configurations	
Wiring Systems	Simplexes (from bottom)
3P	1111
4B	1122
5D	1123
7G	1255
8N	1255
8T	1235
8K	1256



PRODUCT OPTIONS

Wire System	Length	Country of Installation
3P 3-Wire (Plug In)	021, 024, 027, 030, 033, 036, 042, 048, 054, 060, 066, 072, 078, 084, 090, 096, 102, 108, 114, 120, 126, 132, 138, 144	A Canada / U.S.A.
4B 4-Wire		
5D 5-Wire		
7G 7-Wire, Isolated Ground		
8T 8-Wire, Isolated Ground		
8N 8-Wire, Separate Neutral		
8K 8-Wire, Dual Isolated		

SAMPLE ORDER CODE

RLDCC 4B	078	A
-----------------	------------	----------

DIMENSIONS
INCHES / MM

PRICING

L	3-Wire (3P)	4- or 5-Wire (4B or 5D)	7- to 8-Wire (7G to 8K)
21 / 533	n/a	224	231
24 / 610	n/a	228	234
27 / 686	n/a	231	236
30 / 762	n/a	234	241
33 / 838	n/a	236	244
36 / 914	n/a	241	248
42 / 1067	n/a	246	254
48 / 1219	n/a	250	259
54 / 1372	n/a	258	263
60 / 1524	n/a	262	268
66 / 1676	n/a	266	273
72 / 1829	254	272	278
78 / 1981	n/a	277	286
84 / 2134	n/a	282	291
90 / 2286	n/a	289	295
96 / 2438	n/a	294	300
102 / 2591	n/a	299	304
108 / 2743	286	303	309
114 / 2896	n/a	308	316
120 / 3048	n/a	315	321
126 / 3200	n/a	319	326
132 / 3353	n/a	324	331
138 / 3505	n/a	330	337
144 / 3658	316	334	341