Xpress

RLYTU
Tangent Undercabinet Light

This light is mounted to the underside of an overhead cabinet, solid or metal shelf, or elevated desktop cabinet. It provides task lighting for the worksurface.

WHAT'S INCLUDED

1 tangent undercabinet light of specified width, attachment hardware for both metal and wood overhead cabinets (magnets, mounting plates and screws), and 10' cord with detachable power adapter face.

NOTES

Color temperature of 3500K.

Dimming of ON/OFF, 100%, 60%, 30%.

Lifespan of 50,000 hours.

Color Rendering Index (CRI) of 80+.

Generates 900 Lux.

UL/c-UL certified.

Optional PIR Occupancy Sensor with override for on and off.

Input voltage 100 - 240 V.

Output voltage 24 V 1A.

20" wide light can be used with 24" to 84" wide overheads.

23" wide light can be used with 30" to 84" wide overheads.

30" and 33" wide lights can be used with 42" to 84" wide overheads.

40" wide light can be used with overhead 48" to 84" wide overheads.

43" wide light can be used with overhead 54" to 84" wide overheads.



PRODUCT OPTIONS

Accessory Feature	Width	Country of Installation	Finish
0 No Accessory Feature	20, 23, 30, 33, 40, 43	**A** Canada / U.S.A.	**AC** Clear Anodized
1 With Occupancy Sensor			

SAMPLE ORDER CODE

RLYTU 24	20	A	AC

DIMENSIONS INCHES / MM

PRICING

W	NO ACCESSORY FEATURE (0)	WITH OCCUPANCY SENSOR (1)
20 / 508	289	n/a
23 / 584	n/a	367
30 / 762	396	n/a
33 / 838	n/a	472
40 / 1016	503	n/a
43 / 1092	n/a	578