
# Xpress

# XWCT

# Connecting Trapeze Worksurface

Support Configuration



This worksurface is designed for use in linked applications to create 90° application.

## WHAT'S INCLUDED

1 worksurface, reinforcing bar (if applicable) and mounting hardware.

#### WHAT'S EXCLUDED

Supports, Modesty Panel, Casual Linking Devices , Fixed Linking Plates and Power Modules or Duo Grommet – Square.

#### NOTES

This worksurface must be linked to other worksurfaces of the same depth using shared legs. It **cannot** be used as a standalone worksurface.

Not all finishes are available as Xpress, Please see Xpress catalogue and/or specification software for details.

## PRODUCT OPTIONS

Worksurface Thickness	Depth	Width	Angle	Corner Detail	Cut-Out Style	Support Configuration	Worksurface Finish	Edge Trim Style	Edge Trim Finish
<b>D</b> 1" <b>M</b> 1 3/16"	24, 30	36, 42, 48, 54, 60, 66	90	R Radius (Shown)	NN No Cut-Out PC Power/ Data Center Cut-Out - Center SC Square Cut-Out - Center (Shown)	A Thesis Leg (Shown) C C-Leg P Post Leg T T-Leg	Source Laminate Foundation Laminate	6 Straight Trim	Edge Trim Colors

## SAMPLE ORDER CODE

	XWCT M	24	66	90	R	NN	A	LW	6	ST
--	--------	----	----	----	---	----	---	----	---	----

# DIMENSIONS – INCHES FOR MM X BY 25.4

## **PRICING**

			1" (D)	1 3/16" (M)	
D	W	Angle	Source Laminate	Foundation Laminate	
24	36	90	294	383	
24	42	90	319	445	
24	48	90	435	510	
24	54	90	461	575	
24	60	90	486	636	
24	66	90	577	701	
30	36	90	340	479	
30	42	90	370	558	
30	48	90	495	636	
30	54	90	525	715	
30	60	90	555	797	
30	66	90	648	879	