

The Navigate Split Base Feed delivers power from the floor to the Power Module. It is wired to the building power supply in two places for New York City wiring restrictions.

HNBEBFS Navigate Split Base Feed


WHAT'S INCLUDED

1 base feed harness, junction box, I-connector, mounting hardware, additional cover is included when End Condition (E) is specified.

NOTES

In the End Condition (E), the Split Base Feed can connect directly to the Power Module when the I-connector is removed. An additional Power Harness is not required to make this connection.

In the Mid Condition (M), the Split Base Feed module mounts directly to the Frame Link using an additional bracket (included). A 48" Power Harness is required to connect to the Power Module in the Wire Channel.



PRODUCT OPTIONS

Wire System	Length	Style	PVC Option	Country of Installation
8T 8-Wire Isolated Ground	018, 072	E End Condition	Standard	A Canada/USA
8K 8-Wire Dual Isolated		M Mid Condition	V PVC Free	
7T 7-Wire Non Isolated Ground				
7K 7-Wire Dual Non Isolated				

SAMPLE ORDER CODE

HNBEBFS 8K	072	E	V	A
-------------------	------------	----------	----------	----------

DIMENSIONS INCHES / MM

L
18 / 457
72 / 1829

PRICING

ISOLATED GROUND (8T)			
End Condition		Mid Condition	
Standard	PVC Free	Standard	PVC Free
382	420	440	478
454	500	509	543

DUAL ISOLATED (8K)			
End Condition		Mid Condition	
Standard	PVC Free	Standard	PVC Free
485	534	543	592
558	615	615	673

NON ISOLATED GROUND (7T)			
End Condition		Mid Condition	
Standard	PVC Free	Standard	PVC Free
382	420	440	478
454	500	509	543

DUAL NON ISOLATED (7K)			
End Condition		Mid Condition	
Standard	PVC Free	Standard	PVC Free
485	534	543	592
558	615	615	673