

The Base Feed is used to route power from the floor to the Power Module.

WHAT'S INCLUDED


1 base feed with bracket (s), i-connector, mounting hardware.

NOTES

In the Mid Condition (M), the Base Feed mounts to the Frame Link using an additional bracket (included). A 48" Power Harness is required to connect to the Power Module in the Wire Channel.

HNBEBF

Navigate Base Feed



PRODUCT OPTIONS

Wire System		Length	Style		Cover Finish	PVC Option	Country of Installation	
8T	8-Wire Isolated Ground	072, 144	E	End Condition	Foundation	Standard	A	Canada/USA
8K	8-Wire Dual Isolated		M	Mid Condition	Mica Accent	V PVC Free		
7T	7-Wire Non Isolated Ground							
7K	7-Wire Dual Non Isolated							

SAMPLE ORDER CODE

HNBEBF 8K	072	E	91	V	A
-----------	-----	---	----	---	---

DIMENSIONS
INCHES / MM

L
72 / 1829
144 / 3658

PRICING

ISOLATED GROUND (8T)				DUAL ISOLATED (8K)			
END CONDITION		MID CONDITION		END CONDITION		MID CONDITION	
Standard	PVC Free	Standard	PVC Free	Standard	PVC Free	Standard	PVC Free
438	484	499	544	551	606	610	665
575	633	634	690	716	789	776	846
NON ISOLATED GROUND (7T)				DUAL NON ISOLATED (7K)			
END CONDITION		MID CONDITION		END CONDITION		MID CONDITION	
Standard	PVC Free	Standard	PVC Free	Standard	PVC Free	Standard	PVC Free
438	484	499	544	551	606	610	665
575	633	634	690	716	789	776	846