

The Base Feed is used to route power from the floor to the Power Module.


WHAT'S INCLUDED

1 base feed with bracket (s), i-connector, mounting hardware.

NOTES

In the Mid Condition (M), the Base Feed mounts to the Frame Link using an additional bracket (included). A 48" Power Harness is required to connect to the Power Module in the Wire Channel.

HNBEBF
Navigate Base Feed



PRODUCT OPTIONS

Wire System	Length	Style	Cover Finish	PVC Option	Country of Installation	
8T 8-Wire Isolated Ground	072, 144	E End Condition	Foundation	Standard	A Canada/USA	
8K 8-Wire Dual Isolated		M Mid Condition	Mica Accent	V PVC Free		
7T 7-Wire Non Isolated Ground						
7K 7-Wire Dual Non Isolated						

SAMPLE ORDER CODE

HNBEBF 8K	072	E	91	V	A
------------------	------------	----------	-----------	----------	----------

DIMENSIONS
INCHES / MM

L
72 / 1829
144 / 3658

PRICING

ISOLATED GROUND (8T)			
END CONDITION		MID CONDITION	
Standard	PVC Free	Standard	PVC Free
422	466	480	524
553	609	610	664

DUAL ISOLATED (8K)			
END CONDITION		MID CONDITION	
Standard	PVC Free	Standard	PVC Free
530	583	587	640
689	759	747	814

L
72 / 1829
144 / 3658

NON ISOLATED GROUND (7T)			
END CONDITION		MID CONDITION	
Standard	PVC Free	Standard	PVC Free
422	466	480	524
553	609	610	664

DUAL NON ISOLATED (7K)			
END CONDITION		MID CONDITION	
Standard	PVC Free	Standard	PVC Free
530	583	587	640
689	759	747	814