


## HNBEP C

### Navigate Power Conservation System



The Navigate Power Conservation System provides an automatic power switch to workstation outlets on circuit 1 and 2.

#### WHAT'S INCLUDED

1 control box, sensors (specified quantity), connection brackets, cables, 4-way splitter, mounting hardware.

#### NOTES

Automatic shut-off timer is factory set at 20 minutes.

Sensor connection cables finished in Grey and White.

System Control Box finished in Platinum.

System control box is available in Platinum (Foundation) only. Each Control Box offers two separate output jack for connection of Occupancy Sensors. The first output jack controls power to all receptacles on Teknion Circuit 1 and the second output jack controls power to all receptacles on Teknion Circuit 2. Each of the output jacks is labeled on the control box.

Always specify one sensor per workstation.

Only one controlled circuit per workstation (do not specify two controlled circuits in one single workstation).

Do not specify mix receptacles for both circuit 1 and 2 in a single workstation.

#### PRODUCT OPTIONS

Application	Frame Module Size	Number of Sensors	Cover Finish
D Back-to-Back Installation	SM Frame Modules 60" or Less	2 Two	Foundation Mica
	LG Frame Modules 66" or More	4 Four	
		8 Eight	

#### SAMPLE ORDER CODE

<b>HNBEP C D</b>	<b>LG</b>	<b>2</b>	<b>25</b>
------------------	-----------	----------	-----------

#### PRICING

	Two Sensors (2)	Four Sensors (4)	Eight Sensors (8)
Frame Modules 60" or Less (SM)	1791	2205	3037
Frame Modules 66" or More (LG)	2011	2426	3256

