


HWBEAP  
hiSpace Surface Access Power Box



The hiSpace Surface Access Power Box is to be paired with a hiSpace Rectangular Worksurface with Center Access Door cut out and a hiSpace Center Access Door to create a worksurface integrated user power solution.

WHAT’S INCLUDED

Surface access power box, power cord with specified length.

NOTES

Requires Center Access Door cut out to be specified in the applicable worksurface.

Requires Center Access Door.

Pilot holes are present for installation on the underside of the worksurface when the Center Access Door cut out is specified.

Always includes a data cover plate.

Data cover plate finished in Platinum Coordinate.

USB-A port supplies 10 Watts (5VDC) when used in single port mode.

USB-C port supplies 18 Watts (5/9/12VDC) when used in single port mode.

USB-C port will support Quick Charge when used in single port mode.

When both ports are used at the same time, output may be reduced.

PRODUCT OPTIONS

Application		Configuration	Power Cord Length	Cord & Plug Type
01	HAB - Center Access Door Cut Out	T3000	Triple - 3 Power	A
		T2110	Triple - 2 Power / 1 USB-A / 1 USB-C	
			P108 Plug-In with 9 ft cord P120 Plug-In with 10 ft cord P180 Plug-In with 15 ft cord	

SAMPLE ORDER CODE

HWBEAP 01	T3000	P120	A
-----------	-------	------	---

DIMENSIONS  
INCHES / MM

Configuration	Plug-In with 9 ft Cord	Plug-In with 10 ft Cord	Plug-In with 15 ft Cord
T3000	484	484	522
T2110	539	539	576

PRICING