


W W E B F
Base Feed



The Base Feed is used to route power from the floor to a Power Module.

WHAT'S INCLUDED
1 base feed, i-connector plus additional 24" mesh harness (if frame module size (LG) is selected).

NOTES
The Base Feed is mounted to the underside of the center support beam in a double-sided application then connects to a Power Module.
For a Single-Sided Bench, it attaches to the Modesty Panel.
In a Table application, the Base Feed mounts directly to the bottom worksurface.
Available in, 8-Wire Isolated Ground (8T), 7-Wire Non Isolated Ground (7T), 8-Wire Dual Ground (8K) and 7-Wire Dual Non Isolated (7K) wiring systems.
It has a 72" or 144" cable on the opposite side which is hardwired to the power source in the floor.
If Bench Frame Modules are longer than 60", an I-Connector and an additional 24" Mesh Power Harness will be provided to reach directly to the Power Module (WWEPM).
For Table Mount (T) Style, use Frame Module Size (SM).

PRODUCT OPTIONS

Wire System	Length	Frame Module Size	Mounting Style	Country of Installation	PVC Free Option
8T 8-Wire Isolated Ground	72, 144	SM For Frame Modules 60" or Less	S For Mounting on a Single-Sided Frame	A Canada/USA	~ Standard V PVC Free
8K 8-Wire Dual Isolated		LG For Frame Modules 66" or More	D For Mounting on a Double-Sided Frame		
7T 7-Wire Non Isolated Ground			T For Mounting on a Table		
7K 7-Wire Dual Non Isolated					

SAMPLE ORDER CODE

WWEBF 8K	72	LG	D	A	V
----------	----	----	---	---	---

DIMENSIONS

L
72 / 1829
144 / 3658

PRICING

8-WIRE ISOLATED GROUND (8T) & 7-WIRE NON ISOLATED GROUND (7T)			
FRAME MODULE 60" OR LESS		FRAME MODULE 66" OR MORE	
Standard	PVC Free	Standard	PVC Free
476	523	660	709
620	681	805	867
8-WIRE DUAL ISOLATED (8K) & 7-WIRE DUAL NON ISOLATED (7K)			
FRAME MODULE 60" OR LESS		FRAME MODULE 66" OR MORE	
Standard	PVC Free	Standard	PVC Free
597	655	781	838
776	853	961	1035