


W W E R O

Receptacle Outlet



The Receptacle Outlet mounts onto the Power Module to provide access to power.

WHAT'S INCLUDED

1 duplex.

NOTES

Specified individually for maximum circuit flexibility.

Two receptacles can be mounted to each side of the Power Module (WWEPM).

Styles include Standard 15 amp, T-Slot 20 amp, USB, Controlled 15 and 20 amp.

Outlet configurations consist of Circuit 1, Circuit 2, Circuit 3 (use 7T and 8T only), Circuit 5 (8T and 8K only), Circuit 6 (use 8K only), Circuit A (7T and 7K only), Circuit B (7K only) and USB.

Receptacle style D and E include a marking indicating it is connected to a control system.

Available in 15 amp and 20 amp.

If Receptacle Style USB 5 VDC 2.1 Amp (U) is selected, Circuits 2, 3, 5 & 6, A, B are not available.

PRODUCT OPTIONS

Receptacle Style	Outlet Configuration	Country of Installation	Receptacle Color
S Standard 15 Amp	1 Circuit 1	A Canada/USA	YY Ebony
T T-Slot 20 Amp	2 Circuit 2		YF Storm White
U USB 5 VDC 2.1 Amp	3 Circuit 3 (Use with 7T & 8T only)		YN Platinum Grey Coordinate
D Controlled 15 Amp	5 Circuit 5 (use with 8T & 8K only)		YV Very White Coordinate
E Controlled 20 Amp	6 Circuit 6 (Use with 8K only)		
	A Non Isolated Ground Circuit (use with 7T & 7K only)		
	B Non Isolated Ground Circuit (use with 7K only)		

SAMPLE ORDER CODE

W W E R O S	6	A	YF
--------------------	----------	----------	-----------

RECEPTACLE STYLE

PRICING

S	37
T	42
U	174
D	37
E	42