


**Xpress**

**E K R O**

## Receptacle Outlet



The Receptacle Outlet mounts onto the Power Module to provide access to power.

**WHAT'S INCLUDED**

1 duplex.

**NOTES**

Specified individually for maximum circuit flexibility.

Styles include Standard 15 amp, T-Slot 20 amp, USB, Controlled 15 and 20 amp.

Outlet configurations consist of Circuit 1, Circuit 2, Circuit 3 (use 7T and 8T only), Circuit 5 (8T and 8K only), Circuit 6 (use 8K only), Circuit A (7T and 7K only), Circuit B (7K only) and USB.

If Receptacle Style USB 5 VDC 2.1 Amp (U) is selected, Circuits 2, 3, 5 and 6, A, B are not available.

Receptacle style D and E include a marking indicating it is connected to a control system.

**Xpress** Available through *Teknion's Xpress Program*.

**PRODUCT OPTIONS**

Receptacle Style	Outlet Configuration (Single-Sided)	Country of Installation	Finish
<b>S</b> Standard 15 Amp	<b>1</b> Circuit 1	<b>A</b> Canada/U.S.A.	<b>YY</b> Ebony
<b>T</b> T-Slot 20 Amp	<b>2</b> Circuit 2		<b>YF</b> Storm White
<b>U</b> USB (Circuit 1 only)	<b>3</b> Circuit 3 (for use with 7T & 8T)		<b>YN</b> Platinum Grey Coordinate
<b>D</b> Controlled 15 Amp	<b>5</b> Circuit 5 (use with 8T & 8K only)		<b>YV</b> Very White Coordinate
<b>E</b> Controlled 20 Amp	<b>6</b> Circuit 6 (for use with 8K)		
	<b>A</b> Circuit A Non Isolated Ground (use with 7T & 7K only)		
	<b>B</b> Circuit B Non Isolated Ground (use with 7K only)		

**SAMPLE ORDER CODE**

<b>EKRO S</b>	<b>5</b>	<b>A</b>	<b>YF</b>
---------------	----------	----------	-----------

**RECEPTACLE STYLE**

**PRICING**

S	42
T	51
U	208
D	42
E	51