


## KEUW

### Monolithic Wood Element - Power/Communication



The Monolithic Wood Element – Power/Communication provides face mounted access to power and/or communication.

#### WHAT'S INCLUDED

1 wood power/communication element.

**Power only (1):** 2 power bezels, 1 cut out with a cap (only 1 power bezel on elements 30" wide or less).

**Power and Communications (2):** 2 power bezels, 1 communication bezel with cover plate (only 1 power bezel on elements 30" wide or less).

**Communications only (3):** 1 communication bezel with cover plate and 2 cut outs with caps (only 1 power bezel on elements 30" wide or less).

#### NOTES

Wood Power/Communication Elements are only compatible with power/communication boxes.

Wood finish creates a large panel monolithic wood aesthetic.

\* Bezel will have a Black finish, unless otherwise specified.

See Application pages for power & communication location restrictions.

Available in Standard (S) and Corridor (C) width applications.

#### PRODUCT OPTIONS

Application	Configuration	Height	Width (in 6" increments)	Power/ Communications Location	Finish	* Bezel Finish
<b>S</b> Standard Width	<b>1</b> Power Only	36, 45	24 - 48	<b>B</b> Bottom	Flintwood	<b>YF</b> Storm White Coordinate
<b>C</b> Corridor Width	<b>2</b> Power and Communications			<b>U</b> Under Worksurface		<b>YN</b> Platinum Grey Coordinate
	<b>3</b> Communications Only			<b>A</b> Above Worksurface		<b>YY</b> Ebony
	<b>4</b> CALA Power and Communication Two Outlets			<b>T</b> Top		<b>YV</b> Very White Coordinate
	<b>5</b> CALA Power and Communication Four Outlets					

352

#### SAMPLE ORDER CODE

<b>KEUW C</b>	<b>2</b>	<b>36</b>	<b>48</b>	<b>B</b>	<b>FD</b>	<b>YN</b>
---------------	----------	-----------	-----------	----------	-----------	-----------

#### DIMENSIONS INCHES / MM

H	W
36 / 914	24 / 610
36 / 914	30 / 762
36 / 914	36 / 914
36 / 914	42 / 1067
36 / 914	48 / 1219
45 / 1143	24 / 610
45 / 1143	30 / 762
45 / 1143	36 / 914
45 / 1143	42 / 1067
45 / 1143	48 / 1219

#### PRICING

448
498
548
598
646
498
559
619
679
742

If Configuration Option 4 add 24

If Configuration Option 5 is selected add 30