


HTEFP
Flexible Power Module



A Flexible Power Modules provides two duplexes mounted to the Power Rail on one side of the Stage. It's location is user adjustable along the Power Rail.

WHAT'S INCLUDED

1 flexible power module (2 duplexes), mounting brackets.

NOTES

Power Module and Duplexes available in a Very White and Gris finish.

PVC option available.

USB Receptacle Style is only available for Circuit one.

Receptacle finish will automatically match the finish option selected.

PRODUCT OPTIONS

Wire Systems	Cable Length	Receptacle Style	Receptacle Style	
8T 8-Wire Isolated Ground	024, 036, 048	S Standard 15 Amp	1A Circuit 1 & A (Use with 7T & 7K Only)	16 Circuit 1 & 6 (use with 8K only)
8K 8-Wire Dual Isolated		T T-Slot 20 Amp	1B Circuit 1 & B (Use with 7K Only)	22 Circuit 1 & 2
7T 7-Wire Non Isolated Ground			2A Circuit 2 & A (Use with 7T & 7K Only)	23 Circuit 2 & 3 (use with 8T only)
7K 7-Wire Dual Non Isolated			3A Circuit 3 & A (Use with 7T Only)	25 Circuit 2 & 5
			AA Circuit A (Use with 7T & 7K Only)	26 Circuit 2 & 6 (use with 8K only)
			AB Circuit A & B (Use with 7T & 7K Only)	33 Circuit 3 & 3 (use with 8T only)
			BB Circuit B (Use with 7K Only)	35 Circuit 3 & 5 (use with 8T only)
			11 Circuit 1	55 Circuit 5 & 5
			12 Circuit 1 & 2	56 Circuit 5 & 6 (use with 8K only)
			13 Circuit 1 & 3 (use with 8T only)	66 Circuit 6 & 6 (use with 8K only)
			15 Circuit 1 & 5	U1 USB & Circuit 1

SAMPLE ORDER CODE

HTEFP 8T	036	T	U1
-----------------	------------	----------	-----------

PRODUCT OPTIONS (CONTINUED)

Country of Installation	Finish	PVC Option
A Canada/USA	26 Soft Gris 83 Very White	Standard V PVC Free

SAMPLE ORDER CODE (CONTINUED)

A	26	V
----------	-----------	----------

See Pricing on the following page.

H T E F P Flexible Power Module (Continued)

DIMENSIONS INCHES / MM

L
024 / 610
036 / 915
048 / 1219

PRICING

8-WIRE ISOLATED GROUND (8T) & 7-WIRE NON ISOLATED GROUND (7T)

Standard 15 Amp, Circuits	T-Slot 20 Amp, Circuits
390	462
401	479
420	492

8-WIRE DUAL ISOLATED (8K) & 7-WIRE DUAL NON ISOLATED (7K)

Standard 15 Amp, Circuits	T-Slot 20 Amp, Circuits
401	479
420	492
432	507

If PVC Free is specified, add 97

If USB is specified, add 121