


Y G U

Navigate Height-Adjustable
Built-In Base

One Table
One Plug



Navigate Height-Adjustable Built-In Base is for use with upStage Modules and Credenzas for Height-Adjustable Tables.

WHAT'S INCLUDED

1 electric height-adjustable table base, leg and foot configuration as specified.

NOTES

Electric base mechanism has 0.1 Watt resting power draw and uses 120V North American control box.

For Switch details, see the Application Guide section.

Vertical Wire Carrier includes Cross-Channel bracket and mounts into Module.

Cross Channel Integrated Powerbar option (C) includes 3 outlets + 1 IEC Connection. This IEC connection accepts only one IEC-compatible power accessory (with an IEC cord terminal) at a time.

Undersurface cable management option (5) - Dual Plastic Trays + Powerbar with IEC refers to a Power Rod (with IEC cord terminal) that must be plugged into the IEC connection of the Cross Channel Integrated Powerbar option (C).

For more information about the One Table One Plug electrical system, IEC-compatible power accessories and planning with IEC Connection, refer to Complements: *Teknion's Ergonomics & Accessories Program*.

PRODUCT OPTIONS

Leg Application		Base Mechanism	Actual Depth	Actual Width	Foot Style
TML	T-Legs (Left Leg Corridor, Right Leg Stage Module)	7S Standard Range Electric (27" - 43") 9C Extended Electric-Restricted (25" - 48.7")	25, 30	53, 59, 65, 71, 77, 83	1 Standard
TMR	T-Legs (Right Leg Corridor, Left Leg Stage Module)				
TCL	T-Legs (Left Leg Credenza, Right Leg Stage Module)				
TCR	T-Legs (Right Leg Credenza, Left Leg Stage Module)				
PTL	Post and T-Leg (Left Post Credenza, Right Leg Stage Module)				
PTR	Post and T-Leg (Right Post Credenza, Left Leg Stage Module)				

SAMPLE ORDER CODE

YGU TML	9C	30	65	1
----------------	-----------	-----------	-----------	----------

PRODUCT OPTIONS (CONTINUED)

Base Finish	Switch Style	Switch Finish	Powerbar	Undersurface Cable Management	Vertical Wire Carrier (Optional)
Foundation	S Standard Up/Down	E Ebony Coordinate	N None	N None	N None
Mica	D Display with Up/Down Memory	X Anthracite	I Cross Channel Integrated - 4 Outlets	1 Cable Organizer with Felt Cover	E Ebony Coordinate
Accent	T Toggle Up/Down	7 Platinum	C Cross Channel Integrated - 3 Outlets +1 IEC	3 Dual Plastic Trays and Powerbar	7 Platinum Coordinate
	X Display toggle with Memory and Navigate GPS	6 Crisp Grey		4 Dual Plastic Trays	V Very White Coordinate
				5 Dual Plastic Trays + Powerbar with IEC	

SAMPLE ORDER CODE (CONTINUED)

52	X	X	I	1	N
-----------	----------	----------	----------	----------	----------

See Pricing on the following page.

Y G U

Navigate Height-Adjustable Built-In Base (Continued)

DIMENSIONS INCHES / MM

D	W
25 / 635	53 / 1346
25 / 635	59 / 1499
25 / 635	65 / 1651
25 / 635	71 / 1803
25 / 635	77 / 1956
25 / 635	83 / 2108
30 / 762	53 / 1346
30 / 762	59 / 1499
30 / 762	65 / 1651
30 / 762	71 / 1803
30 / 762	77 / 1956
30 / 762	83 / 2108

D	W
25 / 635	53 / 1346
25 / 635	59 / 1499
25 / 635	65 / 1651
25 / 635	71 / 1803
25 / 635	77 / 1956
25 / 635	83 / 2108
30 / 762	53 / 1346
30 / 762	59 / 1499
30 / 762	65 / 1651
30 / 762	71 / 1803
30 / 762	77 / 1956
30 / 762	83 / 2108

PRICING

STANDARD RANGE ELECTRIC BASE MECHANISM (7S)

Foundation	Mica/Accent
3352	3457
3352	3457
3389	3494
3389	3494
3389	3494
3389	3494
3352	3457
3352	3457
3389	3494
3389	3494
3389	3494
3389	3494

EXTENDED ELECTRIC-RESTRICTED RANGE BASE MECHANISM (9C)

Foundation	Mica/Accent
3579	3684
3579	3684
3593	3699
3593	3699
3593	3699
3593	3699
3579	3684
3579	3684
3593	3699
3593	3699
3593	3699
3593	3699

If Display with Up/Down Memory (D) switch is specified, add 184

If Display Toggle with Memory and Navigate GPS (X) switch is specified, add 184

If Dual Plastic Trays are specified, add 59

If Dual Plastic Trays + Powerbar is specified, add 285

If Cable Organizer with Felt Cover is specified, add 292

If Cross Channel Integrated Powerbar - 4 Outlets (I) or 3 Outlets + 1 IEC (C) with No Cable Management is specified, add 247

If Cross Channel Integrated Powerbar - 4 Outlets (I) or 3 Outlets + 1 IEC (C) + Dual Plastic Trays are specified, add 308

If Cross Channel Integrated Powerbar - 4 Outlets (I) + Dual Plastic Trays + Powerbar are specified, add 533

If Cross Channel Integrated Powerbar - 3 Outlets + 1 IEC (C) + Dual Plastic Trays + Powerbar with IEC are specified, add 605

If Cross Channel Integrated Powerbar - 4 Outlets (I) or 3 Outlets + 1 IEC (C) + Cable Organizer with Felt Cover is specified, add 541

If Vertical Wire Carrier is specified, add 334